

References

- [1] K. Veer, S. Hari, O. Bansal, and D. Singh, “A comprehensive review on hybrid electric vehicles : architectures and components,” *J. Mod. Transp.*, 2019, doi: 10.1007/s40534-019-0184-3.
- [2] “Auto sales trend in FY21: ETAuto Originals: Auto industry’s sales volume trajectory in FY21, Auto News, ET Auto.”
<https://auto.economictimes.indiatimes.com/news/industry/etauto-originals-auto-industrys-sales-volume-trajectory-in-fy21/77495792> (accessed Jun. 05, 2021).
- [3] S. Citation, *Assessment of fuel economy technologies for light-duty vehicles*. 2011.
- [4] “Sources of Greenhouse Gas Emissions | Greenhouse Gas (GHG) Emissions | US EPA.”
<https://www.epa.gov/ghgemissions/sources-greenhouse-gas-emissions> (accessed Mar. 21, 2021).
- [5] “• OECD: oil demand share by sector 2019 | Statista.”
<https://www.statista.com/statistics/307194/top-oil-consuming-sectors-worldwide/> (accessed Mar. 22, 2021).
- [6] “Electric Cars vs Gas Cars: What Do They Cost? | EnergySage.”
<https://www.energysage.com/electric-vehicles/costs-and-benefits-evs/evs-vs-fossil-fuel-vehicles/> (accessed Oct. 05, 2018).
- [7] “Electric cars ‘will be cheaper than conventional vehicles by 2022’ | Environment | The Guardian.” <https://www.theguardian.com/environment/2016/feb/25/electric-cars-will-be-cheaper-than-conventional-vehicles-by-2022> (accessed Oct. 05, 2018).
- [8] B. Propfe *et al.*, “Cost Analysis of Plug-in Hybrid Electric Vehicles including Maintenance & Repair Costs and Resale Values Implementing Agreement on Hybrid and Electric Vehicles,” vol. 5, p. 6862, 2012, doi: 10.3390/wevj5040886.
- [9] *No Titl ãe. .*
- [10] “Electric Cars to Reach Price Parity by 2025 | Bloomberg NEF.”
<https://about.bnef.com/blog/electric-cars-reach-price-parity-2025/> (accessed Oct. 07, 2018).
- [11] A. Panday and H. O. Bansal, “Energy Management Strategy Implementation for Hybrid Electric Vehicles Using Genetic Algorithm Tuned Pontryagin’s Minimum Principle Controller,” *Int. J. Veh. Technol.*, vol. 2016, 2016, doi: 10.1155/2016/4234261.

References

- [12] “Efficiency Compared: Battery-Electric 73%, Hydrogen 22%, ICE 13%.”
<https://insideevs.com/efficiency-compared-battery-electric-73-hydrogen-22-ice-13/>
(accessed Oct. 05, 2018).
- [13] M. Wang *et al.*, “A multifunctional battery module design for electric vehicle,” *J. Mod. Transp.*, vol. 25, no. 4, pp. 218–222, Dec. 2017, doi: 10.1007/s40534-017-0144-8.
- [14] A. Panday and H. O. Bansal, “Green transportation: need, technology and challenges,” *Int. J. Glob. Energy Issues*, vol. 37, no. 5/6, p. 304, 2014, doi: 10.1504/IJGEI.2014.067663.
- [15] F. Badin, J. Scordia, R. Trigui, E. Vinot, and B. Jeanneret, “Hybrid electric vehicles energy consumption decrease according to drive train architecture, energy management and vehicle use,” *IET Hybrid Veh. Conf. 2006*, no. 526, pp. 213–223, 2006, doi: 10.1049/cp:20060610.
- [16] C. E. Sandy Thomas, “Transportation options in a carbon-constrained world: Hybrids, plug-in hybrids, biofuels, fuel cell electric vehicles, and battery electric vehicles,” *Int. J. Hydrogen Energy*, vol. 34, no. 23, pp. 9279–9296, 2009, doi: 10.1016/j.ijhydene.2009.09.058.
- [17] A. Panday and H. O. Bansal, “A Review of Optimal Energy Management Strategies for Hybrid Electric Vehicle,” vol. 2014, 2014.
- [18] M. Eshani, Y. Gao, S. Gay, and A. Emadi, *Modern electric, hybrid electric and fuel cell vehicles 2nd. Edition*. 2010.
- [19] Frost & Sullivan, “Global Electric Vehicle Market Outlook, 2018,” 2018.
<https://store.frost.com/global-electric-vehicle-market-outlook-2018.html> (accessed Oct. 05, 2018).
- [20] R. D. S. G. R. H. N. H. B. Iyer and R. Mangaleswaran, “The future of mobility in India : Challenges & opportunities for the auto component industry,” 2017, Accessed: Oct. 05, 2018. [Online]. Available:
[https://www.mckinsey.com/~media/mckinsey/industries/automotive and assembly/our insights/the future of mobility in india/the-future-of-mobility-in-india.ashx](https://www.mckinsey.com/~media/mckinsey/industries/automotive%20and%20assembly/our%20insights/the%20future%20of%20mobility%20in%20india/the-future-of-mobility-in-india.ashx).
- [21] M. Stanley *et al.*, “Sustainability Compendium : MS Views on Sustainability Topics Morgan Stanley ’ s Sustainability Research Team,” pp. 1–62, 2017.
- [22] Frost & Sullivan, “Global Market Analysis of Plug in Hybrid Electric Vehicles,” *Correspondence*, no. December, 2007.

References

- [23] Singh Sarwant, "Global Electric Vehicle Market Looks To Power Up In 2018." <https://www.forbes.com/sites/sarwantsingh/2018/04/03/global-electric-vehicle-market-looks-to-fire-on-all-motors-in-2018/#5d704852927f> (accessed Oct. 07, 2018).
- [24] S. Rokadiya and A. Bandivadekar, "Hybrid and Electric Vehicles in India – Current Scenario and Market Incentives," *Int. Counc. Clean Transp. (ICCT), Work. Pap.*, no. December, 2016, [Online]. Available: http://www.theicct.org/sites/default/files/publications/India-hybrid-and-EV-incentives_working-paper_ICCT_27122016.pdf.
- [25] P. A. Jennings, R. P. Jones, and A. McGordon, "Generalised Fuzzy-Logic-Based Power Management Strategy for Various Hybrid Electric Vehicle Powertrain Architectures," *UKACC Int. Conf. Control 2010*, pp. 197–202, 2010, doi: 10.1049/ic.2010.0280.
- [26] NPTEL, "Module 3 : Architecture of Hybrid and Electric Vehicles Lecture 5 : Basic Architecture of Hybrid Drive Trains and Analysis of Series Drive Train," *Introd. to Hybrid Electr. Veh. Modul.*, pp. 1–43.
- [27] C. C. Chan, A. Bouscayrol, and K. Chen, "Electric, hybrid, and fuel-cell vehicles: Architectures and modeling," *IEEE Trans. Veh. Technol.*, vol. 59, no. 2, pp. 589–598, 2010, doi: 10.1109/TVT.2009.2033605.
- [28] A. Babu and S. Ashok, "Parallel mild hybrid equivalent to the Tata Safari," *Proc. IEEE Int. Conf. Technol. Adv. Power Energy, TAP Energy 2015*, no. June, pp. 506–510, 2015, doi: 10.1109/TAPENERGY.2015.7229671.
- [29] Yimin Gao, M. Ehsani, and J. Miller, "Hybrid Electric Vehicle: Overview and State of the Art," *Proc. IEEE Int. Symp. Ind. Electron. 2005. ISIE 2005.*, no. 2, pp. 307–316, 2005, doi: 10.1109/ISIE.2005.1528929.
- [30] C. Shen, P. Shan, and T. Gao, "A comprehensive overview of hybrid electric vehicles," *Int. J. Veh. Technol.*, vol. 2011, 2011, doi: 10.1155/2011/571683.
- [31] N. Omar, K. Fleurbaey, C. Kurtulus, P. Van den Bossche, T. Coosemans, and J. Van Mierlo, "SuperLIB project - analysis of the performances of the hybrid Lithium HE-HP architecture for plug-in hybrid electric vehicles," *World Electr. Veh. J.*, vol. 6, no. 2, pp. 259–268, 2013, doi: 10.1109/EVS.2013.6914717.
- [32] X. Li and S. S. Williamson, "Efficiency and suitability analyses of varied drive train architectures for plug-in hybrid electric vehicle (PHEV) applications," *2008 IEEE Veh.*

References

- Power Propuls. Conf. VPPC 2008*, pp. 3–8, 2008, doi: 10.1109/VPPC.2008.4677773.
- [33] M. Ceraolo, A. di Donato, and G. Franceschi, “A general approach to energy optimization of hybrid electric vehicles,” *IEEE Trans. Veh. Technol.*, vol. 57, no. 3, pp. 1433–1441, 2008, doi: 10.1109/TVT.2007.909268.
- [34] J. Meisel, W. Shabbir, and S. A. Evangelou, “Evaluation of the through-the-road architecture for plug-in hybrid electric vehicle powertrains,” *2013 IEEE Int. Electr. Veh. Conf. IEVC 2013*, 2013, doi: 10.1109/IEVC.2013.6681143.
- [35] “Split-Parallel Through-the-Road Hybrid Electric Vehicle : Operation , Power Flow and Control Modes,” 2015.
- [36] S. A. Zulkifli, S. Mohd, N. Saad, and A. R. A. Aziz, “Operation, power flow, system architecture and control challenges of split-parallel through-the-road hybrid electric vehicle,” *2015 10th Asian Control Conf. Emerg. Control Tech. a Sustain. World, ASCC 2015*, 2015, doi: 10.1109/ASCC.2015.7244637.
- [37] J. M. Miller, “Hybrid electric vehicle propulsion system architectures of the e-CVT type,” *IEEE Trans. Power Electron.*, vol. 21, no. 3, pp. 756–767, 2006, doi: 10.1016/j.healun.2006.03.007.
- [38] A. Babu and S. Ashok, “Algorithm for Selection of Motor and Vehicle Architecture for a Plug-in Hybrid Electric Vehicle,” *India Conf. (INDICON), 2012 Annu. IEEE*, no. 1, pp. 875–878, 2012.
- [39] D. G. Taylor, “Systematic Approach to the Modeling and Control of Hybrid Electric Vehicle Powertrains,” pp. 3060–3065.
- [40] J. Shen and A. Khaligh, “An energy management strategy for an EV with two propulsion machines and a hybrid energy storage system,” *2015 IEEE Transp. Electrifi. Conf. Expo, ITEC 2015*, no. 1, pp. 1–5, 2015, doi: 10.1109/ITEC.2015.7165791.
- [41] H. Yin, W. Zhou, M. Li, C. Ma, and C. Zhao, “An Adaptive Fuzzy Logic Based Energy Management Strategy on Battery/Ultracapacitor Hybrid Electric Vehicles,” no. 555, pp. 1–12, 2016, [Online]. Available: http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=7450683.
- [42] L. Idoumghar, D. Fodorean, and A. Miraoui, “Using hybrid constricted particles swarm and simulated annealing algorithm for electric motor design,” *Dig. 2010 14th Bienn. IEEE Conf. Electromagn. F. Comput. CEFC 2010*, no. February, p. 68093, 2010, doi:

References

- 10.1109/CEFC.2010.5481410.
- [43] M. S. ElNozahy and M. M. A. Salama, "Uncertainty-based design of a bilayer distribution system for improved integration of PHEVs and PV arrays," *IEEE Trans. Sustain. Energy*, vol. 6, no. 3, pp. 659–674, 2015, doi: 10.1109/TSTE.2015.2405411.
- [44] M. Zhang, Y. Yang, and C. C. Mi, "Analytical approach for the power management of blended-mode plug-in hybrid electric vehicles," *IEEE Trans. Veh. Technol.*, vol. 61, no. 4, pp. 1554–1566, 2012, doi: 10.1109/TVT.2012.2187318.
- [45] N. K. Pandey, S. Thimmalapura, and P. Isac, "Real world challenges in development of alternate propulsion solutions: An Indian perspective," *2015 IEEE Int. Transp. Electrification Conf. ITEC-India 2015*, 2016, doi: 10.1109/ITEC-India.2015.7386940.
- [46] N. Denis, M. R. Dubois, J. P. F. Trovao, and A. Desrochers, "Power Split Strategy Optimization of a Plug-in Parallel Hybrid Electric Vehicle," *IEEE Trans. Veh. Technol.*, vol. 67, no. 1, pp. 315–326, 2018, doi: 10.1109/TVT.2017.2756049.
- [47] R. Cheng and Z. Dong, "Modeling and Simulation of Plug-In Hybrid Electric Powertrain System for Different Vehicular Application," *2015 IEEE Veh. Power Propuls. Conf. VPPC 2015 - Proc.*, 2015, doi: 10.1109/VPPC.2015.7352976.
- [48] K. L. Butler, M. Ehsani, and P. Kamath, "A Matlab-based modeling and simulation package for electric and hybrid electric vehicle design," *IEEE Trans. Veh. Technol.*, vol. 48, no. 6, pp. 1770–1778, 1999, doi: 10.1109/25.806769.
- [49] S. Inokuchi, M. E. Co, and S. Inokuchi, "A new versatile high power Intelligent Power Module (IPM) for EV and HEV Applications," no. June, pp. 24–26, 2015.
- [50] M. Jang and V. G. Agelidis, "A digitally controlled single-phase buck-boost-inverter using a dual-DSP," *IECON Proc. (Industrial Electron. Conf.)*, pp. 187–192, 2013, doi: 10.1109/IECON.2013.6699133.
- [51] A. Safaee, S. Member, D. Yazdani, and M. Pahlevaninezhad, "Resonant DC-Link Soft-Switched DC-AC Converters," pp. 260–264, 2011.
- [52] S. Liwei, L. Zijian, Z. Qianfan, F. Jianfu, and W. Fuping, "Research of an energy-fed induction motor driving test platform with double inverters for HEV," *VPPC 2007 - Proc. 2007 IEEE Veh. Power Propuls. Conf.*, pp. 531–535, 2007, doi: 10.1109/VPPC.2007.4544181.
- [53] J. Marcinkowski, "Dual-sided cooling of power semiconductor modules," *PCIM Eur.*

References

- Conf. Proc.*, no. May, pp. 1179–1185, 2014.
- [54] S. Adachi, S. Yoshida, H. Miyata, T. Kouge, and D. Inoue, “Automotive power module technologies for high speed switching,” no. May, pp. 10–12, 2016.
- [55] H. Shim *et al.*, “Inverter modeling including non-ideal IGBT characteristics in Hybrid Electric Vehicle for accurate EMI noise prediction,” *IEEE Int. Symp. Electromagn. Compat.*, vol. 2015-Septm, pp. 691–695, 2015, doi: 10.1109/ISEMC.2015.7256247.
- [56] J. Lee, H. Jang, S. Shin, K. Jang, and J. Jung, “Over Temperature Protection in Power Module for Hybrid and Electric Vehicle,” pp. 432–435, 2016.
- [57] P. Han, M. Cheng, S. Zhu, and Z. Chen, “Brushless Doubly-Fed Induction Drive for EV / HEV Applications,” pp. 320–326, 2015.
- [58] T. Dey, K. Mukherjee, and P. Syam, “Dynamic adjustments of the D-Q axes reference voltage limits during flux weakening and MTPA control of an IPMSM drive for an EV application,” *2016 2nd Int. Conf. Control. Instrumentation, Energy Commun. CIEC 2016*, no. 5, pp. 324–328, 2016, doi: 10.1109/CIEC.2016.7513821.
- [59] M. Roche, W. Shabbir, and S. A. Evangelou, “Voltage Control for Enhanced Power Electronic Efficiency in Series Hybrid Electric Vehicles,” *IEEE Trans. Veh. Technol.*, vol. 9545, no. c, pp. 1–14, 2016, doi: 10.1109/TVT.2016.2599153.
- [60] A. K. Gautam, S. P. Singh, J. P. Pandey, and T. N. Shukla, “Performance investigation of Permanent Magnet Synchronous Motor (PMSM) drive supplied from hybrid sources,” *Int. Conf. Emerg. Trends Electr. Electron. Sustain. Energy Syst. ICETEESES 2016*, pp. 292–302, 2016, doi: 10.1109/ICETEESES.2016.7581396.
- [61] P. Winzer and M. Doppelbauer, “A hybrid permanent magnet and wound field synchronous machine with displaced reluctance axis capable of symmetric four quadrant operation,” *2016 18th Eur. Conf. Power Electron. Appl. EPE 2016 ECCE Eur.*, 2016, doi: 10.1109/EPE.2016.7695296.
- [62] M. Boxriker, J. Kolb, and M. Doppelbauer, “Expanding the operating range of permanent magnet synchronous motors by using the optimum number of phases,” *2016 18th Eur. Conf. Power Electron. Appl. EPE 2016 ECCE Eur.*, 2016, doi: 10.1109/EPE.2016.7695597.
- [63] T. Senanayake, R. Iijima, T. Isobe, and H. Tadano, “Z-source with rectangular wave modulation inverter for Hybrid/Electric vehicles,” in *2016 18th European Conference on*

References

- Power Electronics and Applications (EPE'16 ECCE Europe)*, Sep. 2016, pp. 1–10, doi: 10.1109/EPE.2016.7695682.
- [64] H. Ye, B. Bilgin, and A. Emadi, “Reduced-parts three-phase inverters: A comparative study,” *2012 IEEE Transp. Electrification Conf. Expo, ITEC 2012*, pp. 8–13, 2012, doi: 10.1109/ITEC.2012.6243455.
- [65] Z. Wu and G.-J. Su, “High-performance permanent magnet machine drive for electric vehicle applications using a current source inverter,” *Ind. Electron. 2008. IECON 2008. 34th Annu. Conf. IEEE*, pp. 2812–2817, 2008, doi: 10.1109/IECON.2008.4758404.
- [66] C. M. Liaw, “Modified linear model-following controller for current-source inverter-fed induction motor drives,” *IEE Proc. D Control Theory Appl.*, vol. 137, no. 1, p. 49, 1990, doi: 10.1049/ip-d.1990.0005.
- [67] P. N. Enjeti, P. D. Ziogas, and J. F. Lindsay, “A current source PWM inverter with instantaneous current control capability (AC motors),” in *Conference Record of the 1988 IEEE Industry Applications Society Annual Meeting*, pp. 927–933, doi: 10.1109/IAS.1988.25171.
- [68] B. Wu, G. R. Slemon, and S. B. Dewan, “PWM-CSI induction motor drive with phase angle control,” *IEEE Trans. Ind. Appl.*, vol. 27, no. 5, pp. 970–976, 1991, doi: 10.1109/28.90355.
- [69] E. Bassi, F. P. Benzi, S. Bolognani, and G. S. Buja, “A Field Orientation Scheme for Current-Fed Induction Motor Drives Based on the Torque Angle Closed-Loop Control,” *IEEE Trans. Ind. Appl.*, vol. 28, no. 5, pp. 1038–1044, 1992, doi: 10.1109/28.158827.
- [70] T. Ando and M. Nakazato, “Development of a High-Speed Elevator Controlled by Current Source Inverter System with Sinusoidal Input and Output,” *IEEE Trans. Ind. Appl.*, vol. 28, no. 4, pp. 893–899, 1992, doi: 10.1109/28.148457.
- [71] Q. Lei and F. Z. Peng, “Space vector pulsewidth amplitude modulation for a buck-boost voltage/current source inverter,” *IEEE Trans. Power Electron.*, vol. 29, no. 1, pp. 266–274, 2014, doi: 10.1109/TPEL.2012.2225847.
- [72] S. Liu and K. Hameyer, “A current source inverter for battery electric vehicles,” in *2013 15th European Conference on Power Electronics and Applications (EPE)*, Sep. 2013, pp. 1–10, doi: 10.1109/EPE.2013.6631951.
- [73] S. Von Malottki, D. Scharfenstein, and K. Hameyer, “A method to switch off an IPMSM

References

- by a Current-Source-Inverter in the event of a malfunction in a Battery Electric Vehicle,” *2014 16th Eur. Conf. Power Electron. Appl. EPE-ECCE Eur. 2014*, pp. 1–9, 2014, doi: 10.1109/EPE.2014.6910966.
- [74] J. L. J. Liu, H. W. H. Wen, and X. Z. X. Zhang, “Analysis of the VSI with small DC-link capacitor for Electric Vehicles,” *2008 Int. Conf. Electr. Mach. Syst.*, pp. 1401–1405, 2008.
- [75] F. R. Salmasi, T. A. Najafabadi, and P. J. Maralani, “An adaptive flux observer with online estimation of dc-link voltage and rotor resistance for VSI-Based induction motors,” *IEEE Trans. Power Electron.*, vol. 25, no. 5, pp. 1310–1319, 2010, doi: 10.1109/TPEL.2009.2038268.
- [76] G. Feng, C. Lai, and S. Member, “Current Injection based On - line Parameter and VSI Nonlinearity Estimation for PMSM Drives Using Current and Voltage DC Components,” vol. 7782, no. c, pp. 1–9, 2016, doi: 10.1109/TTE.2016.2538180.
- [77] D. N. Badodkar, “Transient Analysis of Three-Phase High-Power Voltage Source Inverter With Nonlinearities in,” vol. 33, no. 4, pp. 3672–3680, 2018.
- [78] A. Bucher *et al.*, “Design of a Full SiC Voltage Source Inverter for Electric Vehicle Applications Siemens AG , eCar Powertrain Systems Keywords,” *18th Eur. Conf. Power Electron. Appl.*, pp. 1–10, 2016, doi: 10.1109/EPE.2016.7695414.
- [79] F. Yao, L. Geng, A. Janabi, and B. Wang, “Impact of modulation schemes on DC-link capacitor of VSI in HEV applications,” *2017 IEEE Int. Electr. Mach. Drives Conf. IEMDC 2017*, 2017, doi: 10.1109/IEMDC.2017.8002186.
- [80] O. Ellabban, J. Van Mierlo, P. Lataire, and B.- Elsene, “Comparison between Different PWM Control Methods for Different Z- Source Inverter Topologies Keywords Review of PWM Control Methods for ZSI Simple Boost Control Modified Space Vector PWM (MSVPWM) Control,” *13th Eur. Conf. Power Electron. Appl.*, 2009.
- [81] A. Moon, “Analysis of Boost converter and Interleaved Converter for Permanent Magnet Synchronous Motor of Hybrid Electrical Vehicle,” pp. 4298–4303, 2016.
- [82] T. Senanayake, R. Iijima, T. Isobe, and H. Tadano, “Z-source with Rectangular wave Modulation Inverter for Hybrid / Electric Vehicles Department of Pure and Applied Sciences , Division of Applied Physics Keywords Motivation Rectangular wave driving with conventional ZSI,” pp. 1–10.
- [83] D. Cao, Q. Lei, and F. Z. Peng, “Development of high efficiency current-fed quasi-Z-

References

- source inverter for HEV motor drive,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 157–164, 2013, doi: 10.1109/APEC.2013.6520201.
- [84] B. C. Charboneau, D. Boroyevich, F. Wang, D. Van Wyk, and E. P. Scott, “DOUBLE-SIDED LIQUID COOLING FOR POWER SEMICONDUCTOR DEVICES USING EMBEDDED POWER TECHNOLOGY,” 2005. Accessed: Oct. 07, 2018. [Online]. Available:
<https://vtechworks.lib.vt.edu/bitstream/handle/10919/31907/CharboneauThesisFinalRevA.pdf;sequence=1>.
- [85] Z. Xu, F. Xu, D. Jiang, W. Cao, and F. Wang, “A high temperature traction inverter with reduced cooling and improved efficiency for HEV applications,” *2013 IEEE Energy Convers. Congr. Expo. ECCE 2013*, pp. 2786–2792, 2013, doi: 10.1109/ECCE.2013.6647062.
- [86] M. Su, C. Chen, S. Sharma, and J. Kikuchi, “Performance and cost considerations for SiC-based HEV traction inverter systems,” *WiPDA 2015 - 3rd IEEE Work. Wide Bandgap Power Devices Appl.*, pp. 347–350, 2015, doi: 10.1109/WiPDA.2015.7369032.
- [87] L. Jin, S. Norrga, H. Zhang, and O. Wallmark, “Evaluation of a multiphase drive system in EV and HEV applications,” *Proc. - 2015 IEEE Int. Electr. Mach. Drives Conf. IEMDC 2015*, pp. 941–945, 2016, doi: 10.1109/IEMDC.2015.7409174.
- [88] S. Inokuchi, S. Saito, and A. Izuka, “A New High Capacity Compact Power Modules for high power EV / HEV inverters,” pp. 468–471, 2016.
- [89] X. Lu, W. Qian, D. Cao, F. Z. Peng, and J. Liu, “A carrier modulation method for minimizing the dc link capacitor current ripple of the HEV DC-DC converter and inverter systems,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 800–807, 2011, doi: 10.1109/APEC.2011.5744687.
- [90] X. Lu and F. Z. Peng, “Theoretical analysis of DC link capacitor current ripple reduction in the HEV DC-DC converter and inverter system using a carrier modulation method,” *2012 IEEE Energy Convers. Congr. Expo. ECCE 2012*, pp. 2833–2839, 2012, doi: 10.1109/ECCE.2012.6342376.
- [91] H. Ye and A. Emadi, “An interleaving scheme to reduce DC-link current harmonics of dual traction inverters in hybrid electric vehicles,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 3205–3211, 2014, doi: 10.1109/APEC.2014.6803764.

References

- [92] S. Norrga, L. Jin, O. Wallmark, A. Mayer, and K. Ilves, “A novel inverter topology for compact EV and HEV drive systems,” *IECON Proc. (Industrial Electron. Conf.)*, pp. 6590–6595, 2013, doi: 10.1109/IECON.2013.6700222.
- [93] J. H. Kim, H. S. Kang, B. K. Lee, and J. Hur, “Cost effective PAM inverter for 42V hybrid electric vehicles (HEV),” *2008 IEEE Veh. Power Propuls. Conf. VPPC 2008*, pp. 1–6, 2008, doi: 10.1109/VPPC.2008.4677605.
- [94] F. Renken *et al.*, “Reliability of high temperature inverters for HEV,” *Fourth Power Convers. Conf. PCC-NAGOYA 2007 - Conf. Proc.*, pp. 563–568, 2007, doi: 10.1109/PCCON.2007.373022.
- [95] H. Akbarian, P. Pillay, and L. Lopes, “Design of a Power Electronic Emulator for Parallel Operation of Renewable Energy Resources in Microgrids,” no. 1, pp. 1532–1537, 2015, doi: 10.1109/IEMDC.2015.7409266.
- [96] V. V. Nair and P. Pathiyil, “High dynamic HIL model for complete software testing solution of Hev/Ev,” *2015 IEEE Int. Transp. Electrification Conf. ITEC-India 2015*, pp. 1–7, 2016, doi: 10.1109/ITEC-India.2015.7386869.
- [97] A. Q. Cai and L. Siek, “A 2-kW, 95% Efficiency Inductive Power Transfer System Using Gallium Nitride Gate Injection Transistors,” *IEEE J. Emerg. Sel. Top. Power Electron.*, vol. 5, no. 1, pp. 458–468, 2017, doi: 10.1109/JESTPE.2016.2632743.
- [98] A. A. S. Mohamed, A. Berzoy, and O. A. Mohammed, “Experimental Validation of Comprehensive Steady-State Analytical Model of Bidirectional WPT System in EVs Applications,” *IEEE Trans. Veh. Technol.*, vol. 66, no. 7, pp. 5584–5594, 2017, doi: 10.1109/TVT.2016.2634159.
- [99] S. Cui and Z. Liu, “Research on Fault Analysis and Fault-Tolerant Control of Electric Motor Drive System in HEV,” *Fuel Cell*, no. 1m, pp. 284–289, 2010, doi: 10.1109/ISCID.2012.248.
- [100] S. Yang, F. Z. Peng, Q. Lei, R. Inoshita, and Z. Qian, “Current-fed quasi-z-source inverter with voltage buck-boost and regeneration capability,” *IEEE Trans. Ind. Appl.*, vol. 47, no. 2, pp. 882–892, 2011, doi: 10.1109/TIA.2010.2102995.
- [101] H. Xu, F. Z. Peng, L. Chen, and X. Wen, “Analysis and design of bi-directional Z-source inverter for electrical vehicles,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 1252–1257, 2008, doi: 10.1109/APEC.2008.4522883.

References

- [102] X. Ding, Z. Qian, S. Yang, B. Cui, and F. Peng, "A New Adjustable-Speed Drives (ASD) System Based on High-Performance Z-Source Inverter," pp. 2327–2332, 2007.
- [103] X. Li and S. S. Williamson, "Efficiency analysis of hybrid electric vehicle (HEV) traction motor-inverter drive for varied driving load demands," *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 280–285, 2008, doi: 10.1109/APEC.2008.4522734.
- [104] H. Khaleghi, A. Yazdian Varjani, and M. Mohamadian, "A new bidirectional zeta DC/DC converter," *PEDSTC 2014 - 5th Annu. Int. Power Electron. Drive Syst. Technol. Conf.*, no. Pedstc, pp. 131–136, 2014, doi: 10.1109/PEDSTC.2014.6799358.
- [105] Y. Lai, W. Lee, Y. Lin, and J. Tsai, "Integrated Inverter / Converter Circuit and Control Technique of Motor Drives With Dual-Mode Control for EV / HEV Applications," *Ieee Trans. Power Electron.*, vol. 29, no. 3, pp. 1358–1365, 2014.
- [106] S. George, R. V. Chacko, and S. K., "Modelling and simulation of Electric Vehicle Power train in SEQUEL," *IEEE Int. Conf. Power Electron. Drives Energy Syst.*, 2014, doi: 978-1-4799-6373-7.
- [107] A. Grassmann, O. Geitner, W. Hable, C. Neugirg, F. Winter, and I. Yoo, "Double Sided Cooled Module concept for High Power Density in HEV Applications," *Pcim*, no. May, pp. 19–21, 2015.
- [108] K. T. Chau, Y. S. Wong, and C. C. Chan, "An overview of energy sources for electric vehicles," vol. 40, no. December 1998, 1999, [Online]. Available: http://ac.els-cdn.com/S0196890499000217/1-s2.0-S0196890499000217-main.pdf?_tid=cbf70966-94de-11e4-b275-00000aab0f01&acdnat=1420464715_24b7c27812632e71cd2ea65f352eb39a.
- [109] A. Khaligh and Z. Li, "Battery, ultracapacitor, fuel cell, and hybrid energy storage systems for electric, hybrid electric, fuel cell, and plug-in hybrid electric vehicles: State of the art," *IEEE Trans. Veh. Technol.*, vol. 59, no. 6, pp. 2806–2814, 2010, doi: 10.1109/TVT.2010.2047877.
- [110] L. T. Lam and R. Louey, "Development of ultra-battery for hybrid-electric vehicle applications," *J. Power Sources*, vol. 158, no. 2 SPEC. ISS., pp. 1140–1148, 2006, doi: 10.1016/j.jpowsour.2006.03.022.
- [111] A. Kuperman, I. Aharon, A. Kara, and S. Malki, "A frequency domain approach to analyzing passive battery-ultracapacitor hybrids supplying periodic pulsed current loads,"

References

- Energy Convers. Manag.*, vol. 52, no. 12, pp. 3433–3438, 2011, doi: 10.1016/j.enconman.2011.07.013.
- [112] C. Ashtiani, R. Wright, and G. Hunt, “Ultracapacitors for automotive applications,” *J. Power Sources*, vol. 154, no. 2, pp. 561–566, 2006, doi: 10.1016/j.jpowsour.2005.10.082.
- [113] A. Djellad, P. O. Logerais, A. Omeiri, O. Riou, and J. F. Durastanti, “Optimization of the energy transfer in a system combining photovoltaic source to ultracapacitors,” *Int. J. Hydrogen Energy*, vol. 39, no. 27, pp. 15169–15177, 2014, doi: 10.1016/j.ijhydene.2014.03.144.
- [114] L. Solero, A. Lidozzi, V. Serrao, L. Martellucci, and E. Rossi, “Ultracapacitors for fuel saving in small size hybrid vehicles,” *J. Power Sources*, vol. 196, no. 1, pp. 587–595, 2011, doi: 10.1016/j.jpowsour.2009.07.041.
- [115] B. Hredzak, V. G. Agelidis, and M. Jang, “A model predictive control system for a hybrid battery-ultracapacitor power source,” *IEEE Trans. Power Electron.*, vol. 29, no. 3, pp. 1469–1479, 2014, doi: 10.1109/TPEL.2013.2262003.
- [116] C. G. Hochgraf, J. K. Basco, T. P. Bohn, and I. Bloom, “Effect of ultracapacitor-modified PHEV protocol on performance degradation in lithium-ion cells,” *J. Power Sources*, vol. 246, pp. 1–5, 2012, doi: 10.1016/j.jpowsour.2012.09.038.
- [117] L. Zhang, X. Hu, Z. Wang, F. Sun, and D. G. Dorrell, “Experimental impedance investigation of an ultracapacitor at different conditions for electric vehicle applications,” *J. Power Sources*, vol. 287, pp. 129–138, 2015, doi: 10.1016/j.jpowsour.2015.04.043.
- [118] A. W. Stienecker, T. Stuart, and C. Ashtiani, “An ultracapacitor circuit for reducing sulfation in lead acid batteries for Mild Hybrid Electric Vehicles,” *J. Power Sources*, vol. 156, no. 2, pp. 755–762, 2006, doi: 10.1016/j.jpowsour.2005.06.014.
- [119] M. A. Hannan, M. M. Hoque, A. Mohamed, and A. Ayob, “Review of energy storage systems for electric vehicle applications: Issues and challenges,” *Renew. Sustain. Energy Rev.*, vol. 69, no. January, pp. 771–789, 2017, doi: 10.1016/j.rser.2016.11.171.
- [120] A. Kuperman and I. Aharon, “Battery-ultracapacitor hybrids for pulsed current loads: A review,” *Renew. Sustain. Energy Rev.*, vol. 15, no. 2, pp. 981–992, 2011, doi: 10.1016/j.rser.2010.11.010.
- [121] L. Rambaldi, E. Bocci, and F. Orecchini, “Preliminary experimental evaluation of a four wheel motors, batteries plus ultracapacitors and series hybrid powertrain,” *Appl. Energy*,

References

- vol. 88, no. 2, pp. 442–448, 2011, doi: 10.1016/j.apenergy.2010.08.008.
- [122] A. Burke and M. Miller, “The power capability of ultracapacitors and lithium batteries for electric and hybrid vehicle applications,” *J. Power Sources*, vol. 196, no. 1, pp. 514–522, 2011, doi: 10.1016/j.jpowsour.2010.06.092.
- [123] S. Pay and Y. Baghzouz, “Effectiveness of battery-supercapacitor combination in electric vehicles,” *2003 IEEE Bol. PowerTech - Conf. Proc.*, vol. 3, pp. 728–733, 2003, doi: 10.1109/PTC.2003.1304472.
- [124] J. Shen and A. Khaligh, “Predictive control of a battery/ultracapacitor hybrid energy storage system in electric vehicles,” *2016 IEEE Transp. Electrifi. Conf. Expo, ITEC 2016*, pp. 1–6, 2016, doi: 10.1109/ITEC.2016.7520297.
- [125] W. Lajnef, J. M. Vinassa, O. Briat, and E. Woirgard, “Specification and use of pulsed current profiles for ultracapacitors power cycling,” *Microelectron. Reliab.*, vol. 45, no. 9–11, pp. 1746–1749, 2005, doi: 10.1016/j.microrel.2005.07.102.
- [126] M. McDonough, “Integration of Inductively Coupled Power Transfer and Hybrid Energy Storage System: A Multiport Power Electronics Interface for Battery-Powered Electric Vehicles,” *IEEE Trans. Power Electron.*, vol. 30, no. 11, pp. 6423–6433, 2015, doi: 10.1109/TPEL.2015.2422300.
- [127] A. Panday and H. O. Bansal, “Temperature dependent circuit-based modeling of high power Li-ion battery for plug-in hybrid electrical vehicles,” *2013 Int. Conf. Adv. Technol. Eng. ICATE 2013*, no. 85, 2013, doi: 10.1109/ICAdTE.2013.6524737.
- [128] C. Wang, H. He, Y. Zhang, and H. Mu, “A comparative study on the applicability of ultracapacitor models for electric vehicles under different temperatures,” *Appl. Energy*, vol. 196, pp. 268–278, 2017, doi: 10.1016/j.apenergy.2017.03.060.
- [129] C. Capasso and O. Veneri, “Integration between Super-capacitors and ZEBRA Batteries as High Performance Hybrid Storage System for Electric Vehicles,” *Energy Procedia*, vol. 105, pp. 2539–2544, 2017, doi: 10.1016/j.egypro.2017.03.727.
- [130] P. Bubna, S. G. Advani, and A. K. Prasad, “Integration of batteries with ultracapacitors for a fuel cell hybrid transit bus,” *J. Power Sources*, vol. 199, pp. 360–366, 2012, doi: 10.1016/j.jpowsour.2011.09.097.
- [131] C. Kagiri and X. Xia, “Optimal Control of a Hybrid Battery/Supercapacitor Storage for Neighborhood Electric Vehicles,” *Energy Procedia*, vol. 105, pp. 2145–2150, 2017, doi:

References

- 10.1016/j.egypro.2017.03.605.
- [132] R. Dhaouadi, Y. Hori, and H. Xiaoliang, “Robust control of an ultracapacitor-based hybrid energy storage system for electric vehicles,” *2014 IEEE 13th Int. Work. Adv. Motion Control*, pp. 161–166, 2014, doi: 10.1109/AMC.2014.6823275.
- [133] M. Michalczuk, L. M. Grzesiak, and B. Ufnalski, “Experimental parameter identification of battery-ultracapacitor energy storage system,” *IEEE Int. Symp. Ind. Electron.*, vol. 2015-Septe, pp. 1260–1265, 2015, doi: 10.1109/ISIE.2015.7281653.
- [134] S. Zhang, R. Xiong, and F. Sun, “Model predictive control for power management in a plug-in hybrid electric vehicle with a hybrid energy storage system,” *Appl. Energy*, vol. 185, pp. 1654–1662, 2015, doi: 10.1016/j.apenergy.2015.12.035.
- [135] C. Ma, M.-Y. Chow, H. Razik, and A. Khaligh, “Guest Editorial Special Section on Networked Energy Systems: Architectures, Communication, and Management,” *IEEE Trans. Ind. Informatics*, vol. 12, no. 5, pp. 1896–1899, Oct. 2016, doi: 10.1109/TII.2016.2606250.
- [136] Z. Lei, W. Zhenpo, H. Xiaosong, and D. G. Dorrell, “Residual Capacity Estimation for Ultracapacitors in Electric Vehicles Using Artificial Neural Network,” *IFAC Proc. Vol.*, vol. 47, no. 3, pp. 3899–3904, 2014, doi: 10.3182/20140824-6-ZA-1003.00657.
- [137] Q. Li, W. Chen, Y. Li, S. Liu, and J. Huang, “Energy management strategy for fuel cell/battery/ultracapacitor hybrid vehicle based on fuzzy logic,” *Int. J. Electr. Power Energy Syst.*, vol. 43, no. 1, pp. 514–525, 2012, doi: 10.1016/j.ijepes.2012.06.026.
- [138] F. Jin, M. Wang, and C. Hu, “A fuzzy logic based power management strategy for hybrid energy storage system in hybrid electric vehicles considering battery degradation,” pp. 1–7, 2016, doi: 10.1109/ITEC.2016.7520207.
- [139] J. Liu, Q. Yan, X. Qu, F. Jiang, W. Liu, and Z. Huang, “Explicit Model Predictive Control of Bidirectional DC/DC Converter for Ultracapacitors Energy Storage Unit Applied to Light Rail Vehicle,” *IFAC Proc. Vol.*, vol. 47, no. 3, pp. 10293–10298, 2014, doi: 10.3182/20140824-6-ZA-1003.01216.
- [140] D. Pavkovi, M. Lobrovi, M. Hrgeti, and A. Komljenovi, “A Design of DC Bus Control System for EVs Based on Battery / Ultracapacitor Hybrid Energy Storage,” no. 08, 2014.
- [141] C. Zhao, H. Yin, and M. Fu, “Analysis , Control , and Wireless Charging of Energy Systems Using Ultracapacitors,” 2014.

References

- [142] B. Wang, J. Xu, B. Cao, and X. Zhou, “A novel multimode hybrid energy storage system and its energy management strategy for electric vehicles,” *J. Power Sources*, vol. 281, pp. 432–443, 2015, doi: 10.1016/j.jpowsour.2015.02.012.
- [143] Y. Xing, W. He, M. Pecht, and K. L. Tsui, “State of charge estimation of lithium-ion batteries using the open-circuit voltage at various ambient temperatures,” *Appl. Energy*, vol. 113, pp. 106–115, Jan. 2014, doi: 10.1016/J.APENERGY.2013.07.008.
- [144] J. Snoussi, S. Ben Elghali, R. Outbib, and M. F. Mimouni, “Model Predictive Control For Hybrid Battery / Ultracapacitor Power Supply Used In Vehicular Applications,” pp. 193–200, 2015.
- [145] J. Li, Z. Fu, and X. Jin, “Rule Based Energy Management Strategy for a Battery/Ultracapacitor Hybrid Energy Storage System Optimized by Pseudospectral Method,” *Energy Procedia*, vol. 105, pp. 2705–2711, 2017, doi: 10.1016/j.egypro.2017.03.920.
- [146] H. A. Yavasoglu, C. Shi, S. Member, and K. Gokce, “Energy Storage Systems for EVs with Two Propulsion Machines,” pp. 696–700, 2017.
- [147] A. Kimura, T. Abe, and S. Sasaki, “Drive force control of a parallel-series hybrid system,” *JSAE Rev.*, vol. 20, no. 3, pp. 337–341, 1999, doi: 10.1016/S0389-4304(99)00017-X.
- [148] H. A. Yavasoglu, S. Member, J. Shen, and S. Member, “Power Split Control Strategy for an EV Powertrain With Two Propulsion Machines,” *IEEE Trans. Transp. Electrification*, vol. 1, no. 4, pp. 382–390, 2015, doi: 10.1109/TTE.2015.2504406.
- [149] H. Yin, W. Zhou, M. Li, C. Ma, and C. Zhao, “An Adaptive Fuzzy Logic Based Energy Management Strategy on Battery/Ultracapacitor Hybrid Electric Vehicles,” *IEEE Trans. Transp. Electrification*, vol. 2, no. 3, pp. 300–311, 2016, doi: 10.1109/TTE.2016.2552721.
- [150] E. Chemali *et al.*, “Minimizing Battery Wear in a Battery-Ultracapacitor Hybrid Energy Storage System using a Linear Quadratic Regulator,” *IEEE Conf. Indus. Elect. Soc.*, pp. 3265–3270, 2015.
- [151] Y. Ko, J. Lee, and H. Lee, “A Supervisory Control Algorithm for a Series Hybrid Vehicle With Multiple Energy Sources,” *IEEE Trans. Veh. Technol.*, vol. 64, no. 11, pp. 4942–4953, 2015, doi: 10.1109/TVT.2015.2445872.
- [152] B. Koushki, A. Safaee, P. Jain, and A. Bakhshai, “Review and comparison of bi-directional AC-DC converters with V2G capability for on-board EV and HEV,” *2014 IEEE Transp. Electrification Conf. Expo*, pp. 1–6, 2014, doi: 10.1109/ITEC.2014.6861779.

References

- [153] S. Mane, P. Jagtap, F. Kazi, and N. M. Singh, “Model predictive control of complex switched mode FC-UC hybrid structure,” *2016 Indian Control Conf. ICC 2016 - Proc.*, no. Icc, pp. 66–71, 2016, doi: 10.1109/INDIANCC.2016.7441107.
- [154] P. Thounthong, S. Raël, and B. Davat, “Energy management of fuel cell/battery/supercapacitor hybrid power source for vehicle applications,” *J. Power Sources*, vol. 193, no. 1, pp. 376–385, 2009, doi: 10.1016/j.jpowsour.2008.12.120.
- [155] C. Pitorac, “Using Li-Ion accumulators as traction batteries in the automotive industry. Cost reduction using ultra-capacitors,” *2016 13th Int. Conf. Dev. Appl. Syst. DAS 2016 - Conf. Proc.*, pp. 212–218, 2016, doi: 10.1109/DAAS.2016.7492575.
- [156] A. Mirzaei, A. Jusoh, Z. Salam, E. Adib, and H. Farzanehfard, “Analysis and design of a high efficiency bidirectional DC-DC converter for battery and ultracapacitor applications,” *Simul. Model. Pract. Theory*, vol. 19, no. 7, pp. 1651–1667, 2011, doi: 10.1016/j.simpat.2011.04.007.
- [157] H. Al-Sheikh, O. Bennouna, G. Hoblos, and N. Moubayed, “Power electronics interface configurations for hybrid energy storage in hybrid electric vehicles,” *MELECON 2014 - 2014 17th IEEE Mediterr. Electrotech. Conf.*, no. April, pp. 122–126, 2014, doi: 10.1109/MELCON.2014.6820518.
- [158] M.-E. Choi, S.-W. Kim, and S.-W. Seo, “Energy Management Optimization in a Battery/Supercapacitor Hybrid Energy Storage System,” *IEEE Trans. Smart Grid*, vol. 3, no. 1, pp. 463–472, 2012, doi: 10.1109/TSG.2011.2164816.
- [159] Y. Gurkaynak and A. Khaligh, “Control and Power Management of a Grid Connected Residential Photovoltaic System with Plug-in Hybrid Electric Vehicle (PHEV) Load,” *2009 Twenty-Fourth Annu. IEEE Appl. Power Electron. Conf. Expo.*, no. 1, pp. 2086–2091, 2009, doi: 10.1109/APEC.2009.4802962.
- [160] T. Sarkar and M. Sharma, “A Generalized Approach to Design the Electrical Power System of a Solar Electric Vehicle,” 2014.
- [161] M. Asensio, G. Magallán, and C. De Angelo, “Experimental evaluation of different semi-active configurations for battery-ultracapacitor hybrid energy storage system (HESS),” *2015 16th Work. Inf. Process. Control. RPIC 2015*, 2016, doi: 10.1109/RPIC.2015.7497176.
- [162] B. C. Groen, “Investigation of DC Motors for Electric and Hybrid Electric Motor Vehicle

- Applications Using an Infinitely Variable Transmission,” 2011.
- [163] H. Fathabadi, “Utilizing solar and wind energy in plug-in hybrid electric vehicles,” *Energy Convers. Manag.*, vol. 156, no. November 2017, pp. 317–328, 2018, doi: 10.1016/j.enconman.2017.11.015.
- [164] A. Sivaprasad, J. Joseph, S. Kumaravel, and S. Ashok, “Design and Analysis of a Dual Input DC-DC Converter for Hybrid Electric Vehicle,” no. Mic, 2015.
- [165] H. Farzanehfard, D. S. Beyragh, and E. Adib, “A bidirectional soft switched ultracapacitor interface circuit for hybrid electric vehicles,” *Energy Convers. Manag.*, vol. 49, no. 12, pp. 3578–3584, 2008, doi: 10.1016/j.enconman.2008.07.004.
- [166] L. A. C. Lopes and N. Soleimanpour, “Power losses balancing in a three-level NPC converter driving a PMSM in an electric vehicle,” *2015 IEEE Energy Convers. Congr. Expo. ECCE 2015*, no. 1, pp. 1660–1665, 2015, doi: 10.1109/ECCE.2015.7309894.
- [167] H. Al-Sheikh, O. Bennouna, G. Hoblos, and N. Moubayed, “Modeling, design and fault analysis of bidirectional DC-DC converter for hybrid electric vehicles,” *IEEE Int. Symp. Ind. Electron.*, pp. 1689–1695, 2014, doi: 10.1109/ISIE.2014.6864869.
- [168] I. Andri, J. Fournier, and O. Le, “ScienceDirect ScienceDirect ScienceDirect ScienceDirect Assessing the Daniela feasibility of using temperature function for district heat demand Italy forecast vehicle,” *Energy Procedia*, vol. 148, no. Ati, pp. 106–113, 2018, doi: 10.1016/j.egypro.2018.08.037.
- [169] A. Panday and H. O. Bansal, “A review of optimal energy management strategies for hybrid electric vehicle,” *Int. J. Veh. Technol.*, vol. 2014, 2014, doi: 10.1155/2014/160510.
- [170] A. Panday and H. O. Bansal, “Energy management strategy for hybrid electric vehicles using genetic algorithm,” *J. Renew. Sustain. Energy*, vol. 8, no. 1, 2016, doi: 10.1063/1.4938552.
- [171] A. Panday and H. O. Bansal, “Energy management in hybrid electric vehicles using particle swarm optimization method,” *2016 IEEE 7th Power India Int. Conf. PIICON 2016*, 2017, doi: 10.1109/POWERI.2016.8077236.
- [172] N. Academy, N. Academy, and U. States, “Equilibrium Points in n-Person Games Author (s): John F . Nash Source : Proceedings of the National Academy of Sciences of the United States of America , Published by : National Academy of Sciences Stable URL : <http://www.jstor.org/stable/88031> <http://w>,” vol. 36, no. 1, pp. 48–49, 2010.

References

- [173] V. Isomerism, “L \ 0-0,” vol. 8, no. 8, pp. 2482–2486, 1987.
- [174] F. Zhang, L. Wang, S. Coskun, H. Pang, Y. Cui, and J. Xi, “Energy management strategies for hybrid electric vehicles: Review, classification, comparison, and outlook,” *Energies*, vol. 13, no. 13, 2020, doi: 10.3390/en13133352.
- [175] A. Foles, L. Fialho, and M. Collares-Pereira, “Techno-economic evaluation of the Portuguese PV and energy storage residential applications,” *Sustain. Energy Technol. Assessments*, vol. 39, p. 100686, Jun. 2020, doi: 10.1016/j.seta.2020.100686.
- [176] J. Won, R. Langari, and S. Member, “Intelligent Energy Management Agent for a Parallel Hybrid Vehicle — Part II : Torque Distribution , Charge Sustenance Strategies , and Performance Results,” vol. 54, no. 3, pp. 935–953, 2005.
- [177] S. H. Mahyiddin *et al.*, “Fuzzy logic energy management system of series hybrid electric vehicle,” pp. 10 (6 .)-10 (6 .), 2017, doi: 10.1049/cp.2016.1267.
- [178] M. R. Dubois, A. Desrochers, and N. Denis, “Fuzzy-based blended control for the energy management of a parallel plug-in hybrid electric vehicle,” *IET Intell. Transp. Syst.*, vol. 9, no. 1, pp. 30–37, Feb. 2015, doi: 10.1049/iet-its.2014.0075.
- [179] H. S. Ramadan, M. Becherif, and F. Claude, “Energy Management Improvement of Hybrid Electric Vehicles via Combined GPS/Rule-Based Methodology,” *IEEE Trans. Autom. Sci. Eng.*, vol. 14, no. 2, pp. 586–597, 2017, doi: 10.1109/TASE.2017.2650146.
- [180] T. Deng, P. Tang, Z. Su, and Y. Luo, “Systematic design and optimization method of multi-mode hybrid electric vehicles based on equivalent tree graph,” vol. 8993, no. c, 2020, doi: 10.1109/TPEL.2020.2990209.
- [181] J. Morales-Morales, I. Cervantes, and U. Cano-Castillo, “On the design of robust energy management strategies for FCHEV,” *IEEE Trans. Veh. Technol.*, vol. 64, no. 5, pp. 1716–1728, 2015, doi: 10.1109/TVT.2014.2336214.
- [182] C. Sun, H. He, and F. Sun, “The Role of Velocity Forecasting in Adaptive-ECMS for Hybrid Electric Vehicles,” *Energy Procedia*, vol. 75, pp. 1907–1912, 2015, doi: 10.1016/j.egypro.2015.07.181.
- [183] M. Mohebbi, M. Charkhgard, and M. Farrokhi, “Optimal Neuro-Fuzzy Control of Parallel Hybrid Electric Vehicles,” pp. 252–256, 2005.
- [184] X. Tian, R. He, and Y. Xu, “Design of an Energy Management Strategy for a Parallel Hybrid Electric Bus Based on an IDP-ANFIS Scheme,” *IEEE Access*, vol. 6, pp. 23806–

References

- 23819, 2018, doi: 10.1109/ACCESS.2018.2829701.
- [185] J. Lemieux and Y. Ma, “Vehicle Speed Prediction Using Deep Learning,” *2015 IEEE Veh. Power Propuls. Conf. VPPC 2015 - Proc.*, pp. 1–5, 2015, doi: 10.1109/VPPC.2015.7353037.
- [186] S. Zeynali, N. Rostami, A. Ahmadian, and A. Elkamel, “Two-stage stochastic home energy management strategy considering electric vehicle and battery energy storage system: An ANN-based scenario generation methodology,” *Sustain. Energy Technol. Assessments*, vol. 39, p. 100722, Jun. 2020, doi: 10.1016/j.seta.2020.100722.
- [187] Y. Wu, Y. Zhang, G. Li, J. Shen, Z. Chen, and Y. Liu, “A predictive energy management strategy for multi-mode plug-in hybrid electric vehicles based on multi neural networks,” *Energy*, vol. 208, p. 118366, 2020, doi: 10.1016/j.energy.2020.118366.
- [188] Q. Xu and F. Wang, “Research on the Efficiency Optimization Control of the Regenerative Braking System of Hybrid Electrical Vehicle Based on Electrical Variable Transmission,” *IEEE Access*, vol. 7, pp. 116823–116834, 2019, doi: 10.1109/ACCESS.2019.2936370.
- [189] H. Yu, M. Kuang, and R. McGee, “Trip-oriented Energy Management Control strategy for plug-in hybrid electric vehicles,” *Proc. IEEE Conf. Decis. Control*, pp. 5805–5812, 2011, doi: 10.1109/CDC.2011.6160609.
- [190] H. Budde-Meiwes *et al.*, “A review of current automotive battery technology and future prospects,” *Proc. Inst. Mech. Eng. Part D J. Automob. Eng.*, vol. 227, no. 5, pp. 761–776, 2013, doi: 10.1177/0954407013485567.
- [191] D. N. T. How, M. A. Hannan, M. S. Hossain Lipu, and P. J. Ker, “State of Charge Estimation for Lithium-Ion Batteries Using Model-Based and Data-Driven Methods: A Review,” *IEEE Access*, vol. 7, pp. 136116–136136, 2019, doi: 10.1109/access.2019.2942213.
- [192] “Battery Performance Characteristics - How to specify and test a battery.” <https://www.mpoweruk.com/performance.htm> (accessed Oct. 24, 2019).
- [193] G. Zubi, R. Dufo-López, M. Carvalho, and G. Pasaoglu, “The lithium-ion battery: State of the art and future perspectives,” *Renew. Sustain. Energy Rev.*, vol. 89, pp. 292–308, Jun. 2018, doi: 10.1016/j.rser.2018.03.002.
- [194] “Battery Comparison of Energy Density - Cylindrical and Prismatic Cells.”

References

- <https://www.epectec.com/batteries/cell-comparison.html> (accessed Oct. 24, 2019).
- [195] L. Guo, C. Hu, and G. Li, “The SOC estimation of battery based on the method of improved Ampere-hour and Kalman filter,” *Proc. 2015 10th IEEE Conf. Ind. Electron. Appl. ICIEA 2015*, no. 5, pp. 1458–1460, 2015, doi: 10.1109/ICIEA.2015.7334337.
- [196] C. Weng, J. Sun, and H. Peng, “A unified open-circuit-voltage model of lithium-ion batteries for state-of-charge estimation and state-of-health monitoring,” *J. Power Sources*, vol. 258, pp. 228–237, 2014, doi: 10.1016/j.jpowsour.2014.02.026.
- [197] P. Jansen, M. Vollnhals, D. Renner, D. Vergossen, W. John, and J. Götze, “Advanced binary search pattern for impedance spectra classification for determining the state of charge of a lithium iron phosphate cell using a support vector machine,” *Adv. Radio Sci.*, vol. 14, pp. 55–62, Sep. 2016, doi: 10.5194/ars-14-55-2016.
- [198] D. I. Stroe, V. Knap, M. Swierczynski, T. Stanciu, E. Schaltz, and R. Teodorescu, “An Electrochemical Impedance Spectroscopy Study on a Lithium Sulfur Pouch Cell,” *ECS Trans.*, vol. 72, no. 12, pp. 13–22, Sep. 2016, doi: 10.1149/07212.0013ecst.
- [199] C. Burgos, D. Sáez, M. E. Orchard, and R. Cárdenas, “Fuzzy modelling for the state-of-charge estimation of lead-acid batteries,” *J. Power Sources*, vol. 274, pp. 355–366, Jan. 2015, doi: 10.1016/J.JPOWSOUR.2014.10.036.
- [200] Z. Zhu, D. Liu, Y. Rong, and J. Sun, “Estimation Based on a Second-order LiFePO₄ Battery Model.” 2013, Accessed: May 29, 2019. [Online]. Available: <https://www.semanticscholar.org/paper/Estimation-Based-on-a-Second-order-LiFePO-4-Battery-Zhu-Liu/bb7880e6c1d09d9882f2bb62c127e56cdfd2a69e>.
- [201] Z. He, C. Dong, C. Pan, C. Long, and S. Wang, “State of charge estimation of power Li-ion batteries using a hybrid estimation algorithm based on UKF,” *Electrochim. Acta*, vol. 211, pp. 101–109, 2016, doi: 10.1016/j.electacta.2016.06.042.
- [202] M. Paschero, G. L. Storti, A. Rizzi, F. M. F. Mascioli, and G. Rizzoni, “A Novel Mechanical Analogy-Based Battery Model for SoC Estimation Using a Multicell EKF,” *IEEE Trans. Sustain. Energy*, vol. 7, no. 4, pp. 1695–1702, Oct. 2016, doi: 10.1109/TSTE.2016.2574755.
- [203] A. Fotouhi, K. Propp, D. J. Auger, and S. Longo, “State of Charge and State of Health Estimation Over the Battery Lifespan,” Springer, Cham, 2018, pp. 267–288.
- [204] S. Tong, J. H. Lacap, and J. W. Park, “Battery state of charge estimation using a load-

References

- classifying neural network,” *J. Energy Storage*, vol. 7, pp. 236–243, 2016, doi: 10.1016/j.est.2016.07.002.
- [205] S. Bobba *et al.*, “Life Cycle Assessment of repurposed electric vehicle batteries : an adapted method based on modelling energy flows,” *J. Energy Storage*, vol. 19, no. July, pp. 213–225, 2018, doi: 10.1016/j.est.2018.07.008.
- [206] N. Wassiliadis *et al.*, “Revisiting the dual extended Kalman filter for battery state-of-charge and state-of-health estimation : A use-case life cycle analysis,” *J. Energy Storage*, vol. 19, no. July, pp. 73–87, 2018, doi: 10.1016/j.est.2018.07.006.
- [207] L. Wang, D. Lu, Q. Liu, L. Liu, and X. Zhao, “Electrochimica Acta State of charge estimation for LiFePO₄ battery via dual extended kalman filter and charging voltage curve,” *Electrochim. Acta*, vol. 296, pp. 1009–1017, 2019, doi: 10.1016/j.electacta.2018.11.156.
- [208] W. Zhang, L. Wang, L. Wang, and C. Liao, “An improved adaptive estimator for state-of-charge estimation of lithium- ion batteries,” *J. Power Sources*, vol. 402, no. August, pp. 422–433, 2018, doi: 10.1016/j.jpowsour.2018.09.016.
- [209] Y. Wang, C. Zhang, and Z. Chen, “A method for joint estimation of state-of-charge and available energy of LiFePO₄ batteries,” *Appl. Energy*, vol. 135, pp. 81–87, 2014, doi: 10.1016/j.apenergy.2014.08.081.
- [210] Y. Li, P. Chattopadhyay, S. Xiong, A. Ray, and C. D. Rahn, “Dynamic data-driven and model-based recursive analysis for estimation of battery state-of-charge q ,” *Appl. Energy*, vol. 184, pp. 266–275, 2016, doi: 10.1016/j.apenergy.2016.10.025.
- [211] R. Yang, R. Xiong, H. He, H. Mu, and C. Wang, “A novel method on estimating the degradation and state of charge of lithium-ion batteries used for electrical vehicles,” *Appl. Energy*, vol. 207, pp. 336–345, 2017, doi: 10.1016/j.apenergy.2017.05.183.
- [212] D. Yang, Y. Wang, R. Pan, R. Chen, and Z. Chen, “State-of-health estimation for the lithium-ion battery based on support vector regression,” *Appl. Energy*, vol. 227, no. August 2017, pp. 273–283, 2018, doi: 10.1016/j.apenergy.2017.08.096.
- [213] X. Tang, F. Gao, C. Zou, K. Yao, W. Hu, and T. Wik, “Load-responsive model switching estimation for state of charge of lithium- ion batteries,” *Appl. Energy*, vol. 238, no. January, pp. 423–434, 2019, doi: 10.1016/j.apenergy.2019.01.057.
- [214] G. Liu, C. Xu, H. Li, K. Jiang, and K. Wang, “State of charge and online model

References

- parameters co-estimation for liquid metal batteries,” *Appl. Energy*, vol. 250, no. January, pp. 677–684, 2019, doi: 10.1016/j.apenergy.2019.05.032.
- [215] J. Meng *et al.*, “Low-complexity online estimation for LiFePO₄ battery state of charge in electric vehicles,” *J. Power Sources*, vol. 395, no. March, pp. 280–288, 2018, doi: 10.1016/j.jpowsour.2018.05.082.
- [216] H. Ben Sassi, F. Errahimi, N. Es-Sbai, and C. Alaoui, “Comparative study of ANN/KF for on-board SOC estimation for vehicular applications,” *J. Energy Storage*, vol. 25, p. 100822, Oct. 2019, doi: 10.1016/j.est.2019.100822.
- [217] M. A. Awadallah and B. Venkatesh, “Accuracy improvement of SOC estimation in lithium-ion batteries,” *J. Energy Storage*, vol. 6, pp. 95–104, 2016, doi: 10.1016/j.est.2016.03.003.
- [218] D. Carnevale, C. Possieri, and M. Sassano, “Control Engineering Practice State-of-charge estimation for lead – acid batteries via embeddings and observers,” *Control Eng. Pract.*, vol. 85, no. January, pp. 132–137, 2019, doi: 10.1016/j.conengprac.2019.01.011.
- [219] L. Limn2o4, L.-P. Linicoo2, and L. Li, “Lead Acid NiCad NiMH Zinc Air Aluminium Air Nickel Iron Nickel Zinc Sodium Sulphur Zebra NaNiCl,” 1881, [Online]. Available: <http://www.mpoweruk.com/specifications/comparisons.pdf>.
- [220] “Lithium-based Batteries Information – Battery University.” https://batteryuniversity.com/learn/article/lithium_based_batteries (accessed Nov. 13, 2019).
- [221] S. Jiang, “A Parameter Identification Method for a Battery Equivalent Circuit Model,” *SAE Tech. Pap. Ser.*, vol. 1, 2011, doi: 10.4271/2011-01-1367.
- [222] A. Panday, H. O. Bansal, and P. Srinivasan, “Thermoelectric Modeling and Online SOC Estimation of Li-Ion Battery for Plug-In Hybrid Electric Vehicles,” vol. 2016, 2016.
- [223] H. Rahimi-Eichi, F. Baronti, and M. Y. Chow, “Online adaptive parameter identification and state-of-charge coestimation for lithium-polymer battery cells,” *IEEE Trans. Ind. Electron.*, vol. 61, no. 4, pp. 2053–2061, 2014, doi: 10.1109/TIE.2013.2263774.
- [224] K. S. Ng, C. S. Moo, Y. P. Chen, and Y. C. Hsieh, “State-of-charge estimation for lead-acid batteries based on dynamic open-circuit voltage,” *PECon 2008 - 2008 IEEE 2nd Int. Power Energy Conf.*, no. PECon 08, pp. 972–976, 2008, doi: 10.1109/PECON.2008.4762614.

References

- [225] W.-Y. Chang, “The State of Charge Estimating Methods for Battery: A Review,” *ISRN Appl. Math.*, vol. 2013, no. 1, pp. 1–7, 2013, doi: 10.1155/2013/953792.
- [226] G. S. Misyris, D. I. Doukas, T. A. Papadopoulos, D. P. Labridis, and V. G. Agelidis, “State-of-Charge Estimation for Li-Ion Batteries: A More Accurate Hybrid Approach,” *IEEE Trans. Energy Convers.*, vol. 34, no. 1, pp. 109–119, 2019, doi: 10.1109/TEC.2018.2861994.
- [227] “BU-409: Charging Lithium-ion - Battery University.” <https://batteryuniversity.com/article/bu-409-charging-lithium-ion> (accessed Dec. 23, 2021).
- [228] R. Kumar and H. O. Bansal, “Real-time implementation of adaptive PV-integrated SAPF to enhance power quality,” *Int. Trans. Electr. Energy Syst.*, vol. 29, no. 5, pp. 1–22, 2019, doi: 10.1002/2050-7038.12004.
- [229] M. Palinski, “A Comparison of Electric Vehicles and Conventional Automobiles: Costs and Quality Perspective Title: A Comparison of Electric Vehicles and Conventional Automobiles: Costs and Quality Perspective,” 2017.
- [230] M. Ecker, S. Käbitz, I. Laresgoiti, and D. U. Sauer, “Parameterization of a physico-chemical model of a lithium-ion battery: II. Model validation,” *J. Electrochem. Soc.*, vol. 162, no. 9, pp. A1849–A1857, 2015, doi: 10.1149/2.0541509jes.
- [231] J. Sieg *et al.*, “Fast charging of an electric vehicle lithium-ion battery at the limit of the lithium deposition process,” *J. Power Sources*, vol. 427, no. December 2018, pp. 260–270, 2019, doi: 10.1016/j.jpowsour.2019.04.047.
- [232] M. Al-Zareer, I. Dincer, and M. A. Rosen, “Performance assessment of a new hydrogen cooled prismatic battery pack arrangement for hydrogen hybrid electric vehicles,” *Energy Convers. Manag.*, vol. 173, no. August, pp. 303–319, 2018, doi: 10.1016/j.enconman.2018.07.072.
- [233] M. Al-Zareer, I. Dincer, and M. A. Rosen, “Electrochemical modelling and performance evaluation of a new ammonia-based battery thermal management system for electric and hybrid electric vehicle,” *Electrochim. Acta*, vol. 247, pp. 171–182, 2017, doi: 10.1016/j.electacta.2017.06.162.
- [234] Y. Bicer and I. Dincer, “Comparative life cycle assessment of hydrogen, methanol and electric vehicles from well to wheel,” *Int. J. Hydrogen Energy*, vol. 42, no. 6, pp. 3767–

References

- 3777, 2017, doi: 10.1016/j.ijhydene.2016.07.252.
- [235] K. Hacetoglu, I. Dincer, and M. A. Rosen, “Sustainability assessment of a hybrid energy system with hydrogen-based storage,” *Int. J. Hydrogen Energy*, vol. 40, no. 3, pp. 1559–1568, 2015, doi: 10.1016/j.ijhydene.2014.11.079.
- [236] G. Wu, X. Zhang, and Z. Dong, “Powertrain architectures of electrified vehicles: Review, classification and comparison,” *J. Franklin Inst.*, vol. 352, no. 2, pp. 425–448, 2015, doi: 10.1016/j.jfranklin.2014.04.018.
- [237] L. Serrao, S. Onori, A. Sciarretta, Y. Guezennec, and G. Rizzoni, “Optimal energy management of hybrid electric vehicles including battery aging,” *Proc. Am. Control Conf.*, pp. 2125–2130, 2011, doi: 10.1109/acc.2011.5991576.
- [238] Y. Xing, E. W. M. Ma, K. L. Tsui, and M. Pecht, “Battery management systems in electric and hybrid vehicles,” *Energies*, vol. 4, no. 11, pp. 1840–1857, 2011, doi: 10.3390/en4111840.
- [239] S. N. Kane, A. Mishra, and A. K. Dutta, “Preface: International Conference on Recent Trends in Physics (ICRTP 2016),” *J. Phys. Conf. Ser.*, vol. 755, no. 1, 2016, doi: 10.1088/1742-6596/755/1/011001.
- [240] M. Lelie *et al.*, “Battery management system hardware concepts: An overview,” *Appl. Sci.*, vol. 8, no. 4, 2018, doi: 10.3390/app8040534.
- [241] S. Panchal, I. Dincer, M. Agelin-Chaab, R. Fraser, and M. Fowler, “Design and simulation of a lithium-ion battery at large C-rates and varying boundary conditions through heat flux distributions,” *Meas. J. Int. Meas. Confed.*, vol. 116, no. September 2017, pp. 382–390, 2018, doi: 10.1016/j.measurement.2017.11.038.
- [242] S. Panchal *et al.*, “Cycling degradation testing and analysis of a LiFePO₄ battery at actual conditions,” *Int. J. Energy Res.*, vol. 41, no. 15, pp. 2565–2575, 2017, doi: 10.1002/er.3837.
- [243] G. Xu, W. Li, K. Xu, and Z. Song, “An intelligent regenerative braking strategy for electric vehicles,” *Energies*, vol. 4, no. 9, pp. 1461–1477, 2011, doi: 10.3390/en4091461.
- [244] M. Brandl *et al.*, “Batteries and battery management systems for electric vehicles,” *Proc. - Design, Autom. Test Eur. DATE*, pp. 971–976, 2012, doi: 10.1109/date.2012.6176637.
- [245] S. Barcellona and L. Piegari, “Effect of current on cycle aging of lithium ion batteries,” *J. Energy Storage*, vol. 29, no. February, p. 101310, 2020, doi: 10.1016/j.est.2020.101310.

References

- [246] I. Zilberman, S. Ludwig, M. Schiller, and A. Jossen, “Online aging determination in lithium-ion battery module with forced temperature gradient,” *J. Energy Storage*, vol. 28, no. February, p. 101170, 2020, doi: 10.1016/j.est.2019.101170.
- [247] K. V. Singh, H. O. Bansal, and D. Singh, “Hardware-in-the-loop Implementation of ANFIS based Adaptive SoC Estimation of Lithium-ion Battery for Hybrid Vehicle Applications,” *J. Energy Storage*, vol. 27, no. December 2019, p. 101124, 2020, doi: 10.1016/j.est.2019.101124.
- [248] M. Horn, J. MacLeod, M. Liu, J. Webb, and N. Motta, “Supercapacitors: A new source of power for electric cars?,” *Econ. Anal. Policy*, vol. 61, pp. 93–103, 2019, doi: 10.1016/j.eap.2018.08.003.
- [249] A. Burke and H. Zhao, “Applications of Supercapacitors in Electric and Hybrid Vehicles Applications UCD-ITS-RR-15-09,” *5th Eur. Symp. Supercapacitor Hybrid Solut.*, no. April, 2015.
- [250] L. Kouchachvili, W. Yaïci, and E. Entchev, “Hybrid battery/supercapacitor energy storage system for the electric vehicles,” *J. Power Sources*, vol. 374, no. June 2017, pp. 237–248, 2018, doi: 10.1016/j.jpowsour.2017.11.040.
- [251] T. Zimmermann, P. Keil, M. Hofmann, M. F. Horsche, S. Pichlmaier, and A. Jossen, “Review of system topologies for hybrid electrical energy storage systems,” *J. Energy Storage*, vol. 8, pp. 78–90, 2016, doi: 10.1016/j.est.2016.09.006.
- [252] J. Ronsmans, B. Lalande, and J. S. R. M. N. V, “Fig,” 2015.
- [253] R. Bindu and S. Thale, “Sizing of hybrid energy storage system and propulsion unit for electric vehicle,” *2017 IEEE Transp. Electrification Conf. ITEC-India 2017*, vol. 2018-Janua, pp. 1–6, 2018, doi: 10.1109/ITEC-India.2017.8333846.
- [254] Panasonic, “Find the Right Battery for Your Application,” 2018.
- [255] Maxwell Technologies Inc., “Maxwell K2 ULTRACAPACITORS - 2.7V SERIES,” pp. 1–5, 2014.
- [256] F. Odeim, J. Roes, and A. Heinzl, “Power Management Optimization of an Experimental Fuel Cell/Battery/Supercapacitor Hybrid System,” pp. 6302–6327, 2015, doi: 10.3390/en8076302.
- [257] “Supercapacitor | Types | Capacitor Guide.” <https://eepower.com/capacitor-guide/types/supercapacitor/#> (accessed Jan. 06, 2022).

References

- [258] H. Lee, E. Koo, S. Sul, and J. Kim, “Hyeoun-Dong Lee, Euh-Suh Koo, Seung-Ki Sul, and Joohn-Sheok Kim,” no. December, pp. 33–38, 2000.
- [259] F. U. Syed, M. L. Kuang, M. Smith, S. Okubo, H. Ying, and S. Member, “Fuzzy Gain-Scheduling Proportional – Integral Control for Improving Engine Power and Speed Behavior in a Hybrid Electric Vehicle,” vol. 58, no. 1, pp. 69–84, 2009.
- [260] L. Ippolito, V. Loia, and P. Siano, “Extended Fuzzy C-Means and Genetic Algorithms to Optimize Power Flow Management in Hybrid Electric Vehicles,” *Fuzzy Optim. Decis. Mak.*, vol. 2, no. 4, pp. 359–374, Dec. 2003, doi: 10.1023/B:FODM.0000003954.49357.b3.
- [261] B. Mashadi and S. A. M. Emadi, “Dual-Mode Power-Split Transmission for Hybrid Electric Vehicles,” vol. 59, no. 7, pp. 3223–3232, 2010.
- [262] L. Wu, Y. Wang, X. Yuan, and Z. Chen, “Multiobjective Optimization of HEV Fuel Economy and Emissions Using the Self-Adaptive Differential Evolution Algorithm,” vol. 60, no. 6, pp. 2458–2470, 2011.
- [263] Y. Z. H. Liu, “Fuzzy multi-objective control strategy for parallel hybrid electric vehicle,” vol. 2, no. November 2011, pp. 39–50, 2012, doi: 10.1049/iet-est.2011.0041.
- [264] L. Ming, Y. Ying, L. Liang, L. Yao, and W. Zhou, “Energy management strategy of a plug-in parallel hybrid electric vehicle using fuzzy control,” *Energy Procedia*, vol. 105, pp. 2660–2665, 2017, doi: 10.1016/j.egypro.2017.03.771.
- [265] T. Liu, X. Hu, S. E. Li, and D. Cao, “Reinforcement Learning Optimized Look-Ahead Energy Management of a Parallel Hybrid Electric Vehicle,” vol. 22, no. 4, pp. 1497–1507, 2017.
- [266] M. Dawei, Z. Yu, Z. Meilan, and N. Risha, “Intelligent fuzzy energy management research for a uniaxial parallel hybrid electric vehicle,” *Comput. Electr. Eng.*, vol. 58, pp. 447–464, 2017, doi: 10.1016/j.compeleceng.2016.03.014.
- [267] A. K. Yadav and P. Gaur, “An Optimized and Improved STF-PID Speed Control of Throttle Controlled HEV,” *Arab. J. Sci. Eng.*, vol. 41, no. 9, pp. 3749–3760, 2016, doi: 10.1007/s13369-016-2131-5.
- [268] S. G. Li, S. M. Sharkh, F. C. Walsh, and C. N. Zhang, “Energy and Battery Management of a Plug-In Series Hybrid Electric Vehicle Using Fuzzy Logic,” vol. 60, no. 8, pp. 3571–3585, 2011.

References

- [269] R. Pusca, A. Berthon, and J. Kauffmann, “Fuzzy-logic-based control applied to a hybrid electric vehicle with four separate wheel drives,” pp. 73–81, 2004, doi: 10.1049/ip-cta.
- [270] N. Al-aawar and A. A. Arkadan, “Optimal Control Strategy for Hybrid Electric Vehicle Powertrain,” vol. 03, no. 2, pp. 362–370, 2015.
- [271] X. Wang, L. Li, and C. Yang, “Hierarchical Control of Dry Clutch for Engine-Start Process in a Parallel Hybrid Electric Vehicle,” vol. 2, no. 2, pp. 231–243, 2016.
- [272] R. Ghorbani, E. Bibeau, and S. Filizadeh, “On Conversion of Hybrid Electric Vehicles to Plug-In,” vol. 59, no. 4, pp. 2016–2020, 2016.
- [273] C. Li and G. Liu, “Optimal fuzzy power control and management of fuel cell / battery hybrid vehicles,” vol. 192, pp. 525–533, 2009, doi: 10.1016/j.jpowsour.2009.03.007.
- [274] J. Ryu, Y. Park, and M. Sunwoo, “Electric powertrain modeling of a fuel cell hybrid electric vehicle and development of a power distribution algorithm based on driving mode recognition,” *J. Power Sources*, vol. 195, no. 17, pp. 5735–5748, 2010, doi: 10.1016/j.jpowsour.2010.03.081.
- [275] S. B. Sarkar, Santanu, “International Journal of,” *Int. J. Energy Environ.*, vol. 4, no. 3, pp. 449–458, 2013.
- [276] X. Yuan, C. Zhang, G. Hong, X. Huang, and L. Li, “Method for evaluating the real-world driving energy consumptions of electric vehicles,” *Energy*, vol. 141, pp. 1955–1968, 2017, doi: 10.1016/j.energy.2017.11.134.
- [277] S. Çeven, A. Albayrak, and R. Bayır, “Real-time range estimation in electric vehicles using fuzzy logic classifier,” *Comput. Electr. Eng.*, vol. 83, 2020, doi: 10.1016/j.compeleceng.2020.106577.
- [278] “Internal combustion engine with throttle and rotational inertia and time lag - MATLAB - MathWorks India.”
<https://in.mathworks.com/help/phymod/sdl/ref/genericengine.html?cv=1> (accessed Mar. 22, 2019).
- [279] Q. Gong, Y. Li, and Z. Peng, “Power management of plug-in hybrid electric vehicles using neural network based trip modeling,” *Proc. Am. Control Conf.*, pp. 4601–4606, 2009, doi: 10.1109/ACC.2009.5160623.
- [280] X. Huang, Y. Tan, and X. He, “A torque control strategy with charge buffer for parallel hybrid electric vehicle,” *IEEE Veh. Technol. Conf.*, pp. 1–5, 2010, doi:

References

- 10.1109/VETECF.2010.5594436.
- [281] C. Engineering, V. Optimization, C. Majed, S. H. Karaki, and R. Jabr, “J | C | E Neural Network Technique for Hybrid Electric J | C | E,” pp. 11–23, 2017, doi: 10.22496/jce2016082345.
- [282] P. Zhao, Y. Wang, N. Chang, Q. Zhu, and X. Lin, “A deep reinforcement learning framework for optimizing fuel economy of hybrid electric vehicles,” *Proc. Asia South Pacific Des. Autom. Conf. ASP-DAC*, vol. 2018-Janua, pp. 196–202, 2018, doi: 10.1109/ASPDAC.2018.8297305.
- [283] C. Hou, L. Xu, H. Wang, M. Ouyang, and H. Peng, “Energy management of plug-in hybrid electric vehicles with unknown trip length,” *J. Franklin Inst.*, vol. 352, no. 2, pp. 500–518, 2015, doi: 10.1016/j.jfranklin.2014.07.009.
- [284] C. Majed, S. H. Karaki, and R. Jabr, “Neural Network Technique for Hybrid Electric Vehicle Optimization,” *2016 18th Mediterr. Electrotech. Conf.*, no. April, pp. 1–6, 2016, doi: 10.1109/MELCON.2016.7495327.
- [285] H. Kanchev, N. Hinov, B. Gilev, and B. Francois, “Modelling and Control by Neural Network of Electric Vehicle Traction System,” pp. 23–28, 2018.
- [286] G. Bosque, I. del Campo, and J. Echanobe, “Fuzzy systems, neural networks and neuro-fuzzy systems: A vision on their hardware implementation and platforms over two decades,” *Eng. Appl. Artif. Intell.*, vol. 32, pp. 283–331, Jun. 2014, doi: 10.1016/j.engappai.2014.02.008.
- [287] S. Xie, X. Hu, S. Qi, and K. Lang, “An Artificial Neural Network-Enhanced Energy Management Strategy for Plug-In Hybrid Electric Vehicles,” *Energy*, 2018, doi: 10.1016/j.energy.2018.08.139.
- [288] J. Moreno, M. E. Ortúzar, and J. W. Dixon, “Energy-management system for a hybrid electric vehicle, using ultracapacitors and neural networks,” *IEEE Trans. Ind. Electron.*, vol. 53, no. 2, pp. 614–623, 2006, doi: 10.1109/TIE.2006.870880.
- [289] R. Liu, D. Shi, and C. Ma, “Real-time control strategy of Elman neural network for the parallel hybrid electric vehicle,” *J. Appl. Math.*, vol. 2014, 2014, doi: 10.1155/2014/596326.
- [290] T. Liu, B. Wang, and C. Yang, “Online Markov Chain-based energy management for a hybrid tracked vehicle with speedy Q-learning,” *Energy*, vol. 160, pp. 544–555, 2018, doi:

References

- 10.1016/j.energy.2018.07.022.
- [291] J. Osorio, A. Molina, P. Ponce, and D. Romero, “A Supervised Adaptive Neuro-Fuzzy Inference System controller for a Hybrid Electric Vehicle’s power train system,” *2011 9th IEEE Int. Conf. Control Autom.*, pp. 404–409, 2011, doi: 10.1109/ICCA.2011.6137965.
- [292] K. Rachananjali, K. B. Krishna, S. Suman, and V. Tejasree, *Modeling of an ANFIS Controller for Series – Parallel Hybrid Vehicle*. Springer Singapore, 2018.
- [293] F. M. Frattale Mascioli, A. Rizzi, M. Panella, and C. Bettiol, “Optimization of Hybrid Electric Cars by Neuro-Fuzzy Networks,” *Appl. Fuzzy Sets Theory*, pp. 253–260, 2007, doi: 10.1007/978-3-540-73400-0_31.
- [294] H. Khayyam and A. Bab-Hadiashar, “Adaptive intelligent energy management system of plug-in hybrid electric vehicle,” *Energy*, vol. 69, pp. 319–335, 2014, doi: 10.1016/j.energy.2014.03.020.
- [295] A. Alarcon-rodriguez, G. Ault, and S. Galloway, “Multi-objective planning of distributed energy resources : A review of the,” *Renew. Sustain. Energy Rev.*, vol. 14, no. 5, pp. 1353–1366, 2010, doi: 10.1016/j.rser.2010.01.006.
- [296] I. F. Bouguenna, A. Azaiz, A. Tahour, and A. Larbaoui, “ROBUST NEURO-FUZZY SLIDING MODE CONTROL WITH,” *Energy*, 2018, doi: 10.1016/j.energy.2018.12.101.
- [297] Q. Xu, F. Wang, X. Zhang, and S. Cui, “Research on the Efficiency Optimization Control of the Regenerative Braking System of Hybrid Electrical Vehicle Based on Electrical Variable Transmission,” *IEEE Access*, vol. 7, pp. 116823–116834, 2019, doi: 10.1109/access.2019.2936370.
- [298] M. Najib, M. Salleh, N. Talpur, and K. Hussain, “Adaptive Neuro-Fuzzy Inference System : Overview , Strengths , Limitations , and Solutions,” pp. 527–535, 2017, doi: 10.1007/978-3-319-61845-6.
- [299] “5 Techniques to Prevent Overfitting in Neural Networks.” <https://www.kdnuggets.com/2019/12/5-techniques-prevent-overfitting-neural-networks.html> (accessed Aug. 17, 2020).