

# Table of Contents

|   |             |
|---|-------------|
| <b>List of Figures</b>                                      | <b>xv</b>   |
| <b>List of Tables</b>                                       | <b>xx</b>   |
| <b>List of Abbreviations/Symbols</b>                        | <b>xxii</b> |
| <b>1 Introduction</b>                                       | <b>1</b>    |
| 1.1 Traditional Networks . . . . .                          | 1           |
| 1.2 Software Defined Networking . . . . .                   | 2           |
| 1.2.1 SDN Architecture . . . . .                            | 4           |
| 1.2.2 Controller Configuration . . . . .                    | 5           |
| 1.3 Benefits of SDN . . . . .                               | 6           |
| 1.3.1 Easy to Configure . . . . .                           | 6           |
| 1.3.2 Global Topology View . . . . .                        | 6           |
| 1.3.3 Minimization of Management Cost . . . . .             | 7           |
| 1.3.4 Flexibility . . . . .                                 | 7           |
| 1.4 Contribution of the Thesis . . . . .                    | 8           |
| 1.4.1 Efficient Statistics Collection . . . . .             | 8           |
| 1.4.1.1 Globally Consistent Statistics Collection . . . . . | 8           |
| 1.4.1.2 QoS Parameters Measurement . . . . .                | 9           |
| 1.4.1.3 Optimal Polling Frequency . . . . .                 | 12          |
| 1.4.2 Waypoint Enforcement in Hybrid SDN . . . . .          | 13          |
| 1.5 Other Challenges in SDN . . . . .                       | 15          |
| 1.6 Thesis Organization . . . . .                           | 17          |

|          |  |           |
|----------|--|-----------|
| <b>I</b> | <b>Efficient Statistics Collection in Pure SDN</b>                                       | <b>20</b> |
| <b>2</b> | <b>Collection of Globally Consistent Statistics in Software Defined Networks</b>         | <b>21</b> |
| 2.1      | Introduction . . . . .   | 21        |
| 2.2      | Related Work . . . . .   | 24        |
| 2.3      | OpenSnap . . . . .   | 28        |
| 2.3.1    | System Model . . . . .   | 28        |
| 2.3.2    | Algorithm . . . . .  | 30        |
| 2.3.3    | Correctness . . . . .  | 31        |
| 2.3.3.1  | OpenFlow Based Network With FIFO channels . . . . .                                      | 32        |
| 2.3.3.2  | OpenFlow Based Network With Non-FIFO channels . . . . .                                  | 35        |
| 2.4      | Implementation Details . . . . .   | 35        |
| 2.5      | Experimental Setup And Evaluation . . . . .  | 37        |
| 2.5.1    | Network With FIFO Channels . . . . .   | 37        |
| 2.5.2    | Network With Non-FIFO Channels . . . . .   | 39        |
| 2.6      | Summary . . . . .  | 40        |
| <b>3</b> | <b>Efficient Globally Consistent Statistics Collection for Software-Defined Networks</b> | <b>41</b> |
| 3.1      | Introduction . . . . .   | 41        |
| 3.2      | Issues with Marker-based Mechanisms . . . . .  | 42        |
| 3.3      | GlobeSnap Protocol . . . . .   | 44        |
| 3.3.1    | Overview . . . . .   | 44        |
| 3.3.2    | An Example to Illustrate GlobeSnap Method . . . . .                                      | 46        |
| 3.3.3    | Algorithm at the Controller . . . . .  | 48        |
| 3.3.4    | Need of Two Colors for Switch State . . . . .  | 50        |
| 3.3.5    | Algorithm at Switch . . . . .  | 51        |
| 3.4      | Characteristics of GlobeSnap . . . . .   | 53        |
| 3.4.1    | Consistent Snapshots . . . . .   | 53        |
| 3.4.2    | Near-synchronous Snapshot . . . . .  | 55        |
| 3.4.3    | Efficient and Flexible Recording of Snapshot . . . . .                                   | 55        |
| 3.4.4    | Robustness . . . . .   | 56        |
| 3.4.5    | Estimating Network Parameters from Snapshot . . . . .                                    | 57        |

---

**TABLE OF CONTENTS**

---

|          |   |           |
|----------|---|-----------|
| 3.5      | Overhead . . . . .  | 59        |
| 3.6      | Correctness . . . . .   | 60        |
| 3.7      | Implementation Details . . . . .                                | 65        |
| 3.7.1    | Overview of OpenFlow Features . . . . .                         | 65        |
| 3.7.1.1  | Registers . . . . .   | 65        |
| 3.7.1.2  | Multiple Forwarding Tables Pipeline . . . . .                   | 66        |
| 3.7.2    | Implementing GlobeSnap in OpenFlow . . . . .                    | 66        |
| 3.8      | Experimental Evaluation . . . . .                               | 68        |
| 3.8.1    | Consistency Evaluation . . . . .                                | 69        |
| 3.8.2    | Synchronicity . . . . .   | 72        |
| 3.8.3    | Use Cases of GlobeSnap . . . . .                                | 73        |
| 3.8.3.1  | Identifying Bottleneck Links . . . . .                          | 74        |
| 3.8.3.2  | Computing Packet Loss . . . . .                                 | 75        |
| 3.9      | Summary . . . . .   | 76        |
| <b>4</b> | <b>Queueing Delay Monitoring in OpenFlow Based SDN Networks</b> | <b>77</b> |
| 4.1      | Introduction . . . . .  | 77        |
| 4.2      | Issues and Related Work . . . . .                               | 79        |
| 4.2.1    | Active Delay Monitoring Methods . . . . .                       | 80        |
| 4.2.2    | Passive Delay Monitoring Methods . . . . .                      | 82        |
| 4.3      | System Model . . . . .  | 83        |
| 4.3.1    | Delays . . . . .  | 84        |
| 4.3.2    | Queueing in Traffic Control and linux-htb . . . . .             | 85        |
| 4.3.3    | Queueing Model . . . . .  | 87        |
| 4.3.4    | Estimator for $\bar{W}(t_1, t_2)$ . . . . .                     | 88        |
| 4.3.5    | Confidence Intervals for $\bar{W}(t_1, t_2)$ . . . . .          | 89        |
| 4.3.6    | Calculation of Calibration Constant and Delay . . . . .         | 89        |
| 4.4      | Experimental Setup and Evaluation Criteria . . . . .            | 90        |
| 4.5      | Results . . . . .   | 93        |
| 4.5.1    | Poisson traffic . . . . .                                       | 93        |
| 4.5.2    | Bursty traffic . . . . .  | 95        |

|  |            |
|--|------------|
| 4.6 Implementation Details . . . . .   | 98         |
| 4.7 Summary . . . . .  | 104        |
| <b>5 An Efficient Method to Collect Statistics in SDN Using Curvature Based Sampling</b> | <b>105</b> |
| 5.1 Introduction . . . . .   | 105        |
| 5.2 Related Work . . . . .   | 107        |
| 5.3 Proposed Solution . . . . .  | 108        |
| 5.3.1 Algorithm . . . . .  | 110        |
| 5.3.2 Cost Function . . . . .  | 111        |
| 5.4 Experiments and Evaluation . . . . .   | 112        |
| 5.5 Summary . . . . .  | 118        |
| <b>II Waypoint Enforcement in Hybrid SDN</b>   | <b>119</b> |
| <b>6 Hybrid SDN Survey</b>   | <b>120</b> |
| 6.1 Introduction . . . . .   | 120        |
| 6.2 The Hybrid SDN Paradigm . . . . .  | 122        |
| 6.2.1 What is Hybrid SDN? . . . . .  | 122        |
| 6.2.2 Benefits SDN Promises . . . . .  | 123        |
| 6.2.3 Limitations . . . . .  | 123        |
| 6.2.4 Probable Contextomy . . . . .  | 124        |
| 6.2.4.1 Dual Stack Mode (Hybrid Switch) . . . . .  | 125        |
| 6.2.4.2 OpenFlow Hybrid Mode . . . . .   | 125        |
| 6.3 Hybrid SDN Models . . . . .  | 125        |
| 6.3.1 Co-existence in Control Plane Only . . . . .                                       | 126        |
| 6.3.2 Co-existence in Control and Data Plane . . . . .                                   | 128        |
| 6.4 Comparative Architectural Analysis . . . . .   | 131        |
| 6.4.1 Controller Only . . . . .  | 131        |
| 6.4.2 SDN and Non-SDN islands . . . . .  | 132        |
| 6.4.3 Edge Placements . . . . .  | 132        |

---

## TABLE OF CONTENTS

---

|          |  |            |
|----------|--|------------|
| 6.4.4    | With Middleware . . . . .                                | 133        |
| 6.4.5    | SDN Overlay . . . . .                                    | 133        |
| 6.5      | Implementation Approaches of Hybrid SDN Models . . . . . | 135        |
| 6.5.1    | Controller Only . . . . .                                | 135        |
| 6.5.2    | SDN and Non-SDN Islands . . . . .                        | 138        |
| 6.5.3    | SDN Overlay . . . . .                                    | 138        |
| 6.5.4    | Edge Placements . . . . .                                | 140        |
| 6.5.5    | With Middleware . . . . .                                | 141        |
| 6.5.6    | With Upgrade/Agent . . . . .                             | 142        |
| 6.6      | Addressing Challenges in Hybrid SDN . . . . .            | 144        |
| 6.6.1    | Topology Discovery . . . . .                             | 144        |
| 6.6.2    | Configuration . . . . .                                  | 145        |
| 6.6.3    | The Placement Problem . . . . .                          | 146        |
| 6.6.4    | Conflicts in Hybrid Control Planes . . . . .             | 147        |
| 6.6.5    | Controller-Switch Communication . . . . .                | 148        |
| 6.6.6    | Scalability . . . . .                                    | 149        |
| 6.6.7    | Traffic Engineering . . . . .                            | 149        |
| 6.7      | Summary . . . . .  | 150        |
| <b>7</b> | <b>Waypoint Enforcement in Hybrid SDN</b>                | <b>151</b> |
| 7.1      | Introduction . . . . .                                   | 151        |
| 7.2      | Problem Formulation . . . . .                            | 152        |
| 7.3      | Methods To Achieve Waypoint Enforcement . . . . .        | 156        |
| 7.3.1    | Panopticon . . . . .                                     | 156        |
| 7.3.2    | Telekinesis . . . . .                                    | 158        |
| 7.3.3    | Magneto . . . . .  | 161        |
| 7.4      | A Method for Enhancing Magneto . . . . .                 | 163        |
| 7.4.1    | Performance Evaluation . . . . .                         | 163        |
| 7.5      | Waypoint Enforcement Using Virtual IP . . . . .          | 166        |
| 7.5.1    | Virtual IP Address Mapping . . . . .                     | 167        |
| 7.5.1.1  | One-to-One Mapping . . . . .                             | 167        |

---

**TABLE OF CONTENTS**

|                     |  |            |
|---------------------|--|------------|
| 7.5.1.2             | Cell block based Mapping . . . . .                           | 170        |
| 7.5.1.3             | Subnet Based Mapping . . . . .                               | 172        |
| 7.5.1.4             | Dynamic IP Mapping . . . . .                                 | 174        |
| 7.5.2               | Analysis of the Proposed Method . . . . .                    | 174        |
| 7.5.2.1             | Network Set-Up . . . . .                                     | 174        |
| 7.5.2.2             | Assumptions . . . . .  | 175        |
| 7.5.2.3             | Load on Link . . . . .                                       | 176        |
| 7.5.2.4             | Path length . . . . .  | 179        |
| 7.5.3               | Results . . . . .  | 179        |
| 7.5.3.1             | Load on Different Links . . . . .                            | 180        |
| 7.5.3.2             | Path length . . . . .  | 181        |
| 7.6                 | Analysis and Performance Evaluation of All Methods . . . . . | 181        |
| 7.7                 | Summary . . . . .  | 185        |
| <b>8</b>            | <b>Conclusions and Future Work</b>                           | <b>186</b> |
| 8.1                 | Conclusions . . . . .  | 186        |
| 8.2                 | Future Work . . . . .  | 188        |
| <b>References</b>   |  | <b>190</b> |
| <b>Publications</b> |  | <b>201</b> |
| <b>Biographies</b>  |  | <b>202</b> |