

# Contents

<b>Certificate</b>	<b>i</b>
<b>Declaration</b>	<b>ii</b>
<b>Abstract</b>	<b>iii</b>
<b>Acknowledgements</b>	<b>vi</b>
<b>Contents</b>	<b>ix</b>
<b>List of Figures</b>	<b>xiii</b>
<b>List of Tables</b>	<b>xvi</b>
<b>Abbreviations</b>	<b>xvii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Comparison of Multi-Robot Systems and Swarm Robotic Systems . . . . .	3
1.2 Advantages of Swarm Robotic Systems . . . . .	5
1.3 Potential Applications of SRS and MRS . . . . .	7
1.4 Factors Affecting Widespread Swarming . . . . .	10
1.5 Scope and Objectives of Research Work . . . . .	12
1.6 Organization of the Thesis . . . . .	14
<b>2 Literature Review</b>	<b>16</b>
2.1 Time Synchronization . . . . .	16
2.1.1 Basic Terminologies . . . . .	18
2.1.2 Related Works in Literature . . . . .	20
2.2 Localization in GPS-denied Indoor Environments . . . . .	25
2.2.1 Localization Approaches . . . . .	26
2.2.2 Performance Metrics . . . . .	27
2.2.3 Techniques for Indoor Localization . . . . .	28
2.2.4 Technologies for Indoor Localization . . . . .	30
2.2.4.1 Technologies for Beacon based Localization . . . . .	30
2.2.4.2 Localization under NLOS Conditions . . . . .	32

---

2.2.4.3	Technologies for Self-localization . . . . .	35
2.3	Task Allocation of MRS and SRS Systems . . . . .	36
2.3.1	Different Approaches for Solving MRTA Problem . . . . .	38
2.4	Conclusions . . . . .	41
<b>3</b>	<b>Time Synchronization for SRS and MRS</b>	<b>44</b>
3.1	Introduction . . . . .	44
3.2	Time Synchronization for Swarm of Robots- Desired Characteristics . . . . .	46
3.3	Sources of Errors in Time Synchronization Algorithms- An Analysis . . . . .	47
3.4	Swarm-Sync Framework . . . . .	53
3.4.1	Hardware Architecture . . . . .	55
3.4.2	Swarm-Sync Framework - Time Offset Compensation . . . . .	58
3.4.2.1	Experimental Validation of Time Offset Compensation . . . . .	61
3.4.3	Swarm-Sync framework - Frequency Offset Compensation . . . . .	63
3.4.3.1	Feasibility Analysis of Relative Skew Fingerprinting . . . . .	63
3.4.3.2	Frequency Offset Compensation . . . . .	68
3.4.4	Experimental Validation of Swarm-Sync Framework . . . . .	73
3.4.4.1	Validation for Single-hop Networks . . . . .	73
3.4.4.2	Validation for Multi-hop Networks . . . . .	74
3.5	Comparison of Swarm-Sync Framework with LR, LP and KF and Consensus Based Techniques . . . . .	80
3.5.1	Comparative Analysis with LR, LP, KF Techniques . . . . .	80
Linear Regression (LR)	. . . . .	81
Linear Prediction (LP)	. . . . .	84
Kalman Filter (KF)	. . . . .	85
3.5.2	Comparison with Consensus Based Algorithms . . . . .	87
3.6	Conclusions . . . . .	90
<b>4</b>	<b>Indoor Beacon based Localization of Robots</b>	<b>93</b>
4.1	Introduction . . . . .	93
4.2	Overall Architecture of Beacon Based Localization System . . . . .	95
4.2.1	Localization Procedure . . . . .	100
4.2.1.1	Distance Estimation . . . . .	101
4.2.1.2	Analysis of Position Estimation using Trilateration . . . . .	104
4.3	Location Estimation in LOS/NLOS Conditions . . . . .	106
4.3.1	Artificial Neural Networks- Brief Introduction . . . . .	107
4.3.2	Robust Location Estimation Unit using Two Stage ANN . . . . .	112
4.3.2.1	Dataset Generation for Training of ANN . . . . .	113
4.3.2.2	Selection of ANN Architecture for Location Estimation Unit . . . . .	116
4.3.3	Functional Description of ANN based Location Estimation Unit . . . . .	118
4.4	Performance Analysis of ANN Based Location Estimation Unit . . . . .	122
4.5	Conclusions . . . . .	131
<b>5</b>	<b>Indoor Self-Localization of Robots</b>	<b>134</b>
5.1	Introduction . . . . .	134

5.2	Problem Formulation . . . . .	135
5.3	Introduction to Inertial Measurement Unit . . . . .	136
5.3.1	Sources of Error in IMU Measurements . . . . .	137
5.4	Overall Architecture of the two-dimensional Self-localization System . . . . .	138
5.4.1	Software Architecture of Proposed 2D self-localization Scheme. . . . .	140
5.4.1.1	Input Conditioning . . . . .	140
5.4.1.2	Activity Detection . . . . .	143
5.4.1.3	Fuzzy Logic- A Brief Introduction . . . . .	145
5.4.1.4	Instantaneous Activity Detection . . . . .	148
5.4.1.5	Activity Correlation Unit . . . . .	149
5.4.1.6	Velocity Estimation . . . . .	151
5.4.1.7	Position Estimation . . . . .	152
5.5	Experimental Validation of the IMU based Self-Localization . . . . .	153
5.5.1	Validation of Self-Localization- Test Scenario-1 . . . . .	153
5.5.2	Validation of Self-Localization- Test Scenario-2 . . . . .	155
5.6	Conclusions . . . . .	156
<b>6</b>	<b>Distributed TDMA Based Task Allocation Framework for SRS and MRS</b>	<b>160</b>
6.1	Introduction . . . . .	160
6.2	DTTA Task Allocation Framework . . . . .	162
6.2.1	DTTA for Non-clustered Deployments . . . . .	165
6.2.2	DTTA for Clustered Deployments . . . . .	169
6.3	Introduction to ARGoS Simulator . . . . .	171
6.4	Implementation of DTTA Framework on ARGoS Simulator . . . . .	174
6.4.1	Application Scenario 1 - Small Scale Swarm Task Allocation Scenario. .	174
6.4.2	Application scenario 2 - Medium Scale Swarm Task Allocation Scenario.	178
6.4.3	Complexity Analysis of Task Allocation using DTTA Framework . . . . .	180
6.5	Conclusions . . . . .	182
<b>7</b>	<b>Conclusions and Future Scope</b>	<b>184</b>
7.1	Principal Contributions of the Thesis . . . . .	184
7.2	Limitations and Future Scope . . . . .	189
<b>A</b>	<b>Details of Bswarm Robot</b>	<b>192</b>
<b>B</b>	<b>Hardware Developed for Beacon based Indoor Localization System</b>	<b>195</b>
<b>C</b>	<b>Hardware Set-up for Indoor Self-Localization</b>	<b>197</b>
<b>Bibliography</b>		<b>199</b>
<b>Publications Based on Present Work</b>		<b>212</b>

<b>Brief Biography of the Candidate</b>	<b>213</b>
<b>Brief Biography of the Supervisor</b>	<b>214</b>
<b>Brief Biography of the Co-Supervisor</b>	<b>215</b>