

## Bibliography

---

ABAQUS (2013). *ABAQUS/Standard user's manual*. Hibbit Karlsson, & Sorensen. 13,1057.

Abrate S. Resin flow in fiber preforms. *Appl. Mech. Rev.*. 2002 Nov 1;55(6):579-99.

Almeida, J. H. S., Amico, S. C., Botelho, E. C. and Amado, F. D. R. (2013) 'Hybridization effect on the mechanical properties of curaua/glass fiber composites', *Composites Part B: Engineering*, 55, pp. 492–497. doi: 10.10616/j.compositesb.2013.07.014.

Aruniit, J. Kers, A. Krumme, T. Poltimae, K. Tall, Preliminary study of the influence of post curing parameters to the particle reinforced composite mechanical and physical properties, *Mater. Sci. 18* (2012) 256–261, <http://dx.doi.org/10.5755/j01.ms.18.3.2435>.

ASTM D3379 (1975). Standard test method for tensile strength and Young's modulus for high modulus single filament fibers. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D4255 (1983). Standard test method for in-plane shear properties of polymer matrix composite materials by the rail shear method. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D2344 (2000). Standard test method for short-beam strength of polymer matrix composite materials and their laminates. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D638 (2002). Standard test method for tensile properties of plastics. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D790 (2002). Standard test methods for flexural properties of unreinforced and reinforced plastics and electrical insulating materials. *American Society of Testing and Materials*. Philadelphia, USA.

ASTM D7078 (2005). Standard test method for shear properties of composite materials by V-notched rail shear method. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D3410 (2008). Standard Test Method for Compressive Properties of Polymer Matrix Composite Materials with Unsupported Gage Section by Shear Loading. *American Society for Testing and Materials*, Philadelphia, USA.

ASTM D2584 (2008). Standard test method for ignition loss of cured reinforced resins. *American Society of Testing and Materials*. Philadelphia, USA.

ASTM D3039/D 3039M (2013). Standard Test Method for Tensile Properties of Polymer Matrix Composite Materials. *American Society of Testing and Materials*. Philadelphia, USA.

Al-Salloum, Y. A., H.M. Elsanadedy, A.A. Abadel, Behavior of FRP-confined concrete after high temperature exposure, *Constr. Build. Mater.* 25 (2011) 838–850, <http://dx.doi.org/10.1016/j.conbuildmat.2010.06.103>.

Aleksendri, D., P. Carbone, V. Irovi, Optimization of the temperature-time curve for the curing process of thermoset matrix composites, *Appl. Compos. Mater.* 23 (2016) 1047–1063, <http://dx.doi.org/10.1007/s10443-016-9499-y>.

Badawy, A. A. M., Impact behavior of glass fibers reinforced composite laminates at different temperatures, *Ain Shams Eng. J.* 3 (2012) 105–111, <http://dx.doi.org/10.1016/j.asej.2012.01.001>.

Bang, K.G., J.W. Kwon, D.G. Lee, J.W. Lee, Measurement of the degree of cure of glass fiber-epoxy composites using dielectrometry, *J. Mater. Process. Technol.* 113 (2001) 209–214, [http://dx.doi.org/10.1016/S0924-0136\(01\)00657-4](http://dx.doi.org/10.1016/S0924-0136(01)00657-4).

Barbero, E. J., and Lonetti P (2001) Damage model for composites defined in terms of available data. *Mechanics of Composite Materials and Structures* 8(4): 299–315.

Bailey R, Wood J. Postbuckling behaviour of square compression loaded graphite epoxy panels with square and elliptical cut-outs. *Thin-walled structures*. 1997 Jul 1;28(3-4):373-97.

Barbero EJ and Lonetti P (2002) An inelastic damage model for fiber reinforced laminates. *Journal of Composite Materials* 36(8): 941–962.

Bigg, D. M. (1987) ‘Mechanical Properties of Particulate Filled Polymers’, pp. 115–122.

Bunsell, A. R. and Harris, B. (1974) ‘Hybrid carbon and glass fibre composites’, *Composites*, 5(4), pp. 157–164. doi: 10.1016/0010-4361(74)90107-4.

Babu Kiran, B.V., G. Harish, Effect of thickness on flexural properties of laminated composites, *Int. J. Res. Eng. Adv. Technol.* 1 (2013) 1–9.

Chaowasakoo, T., N. Sombatsompop, Mechanical and morphological properties of fly ash/epoxy composites using conventional thermal and microwave curing methods, *Compos. Sci. Technol.* 67 (2007) 2282–2291, <http://dx.doi.org/10.1016/j.compscitech.2007.01.016>.

Chawla, H. and Singh, S. B. (2018) ‘Stability and failure characterization of fiber reinforced pultruded beams with different stiffening elements, part 2: Analytical and numerical studies’, *Thin-Walled Structures*. Elsevier Ltd, (October), pp. 1–21. doi: 10.1016/j.tws.2018.10.024.

Chawla, K. K. (2012) *Composite Materials, Materials Handbook*. doi: 10.1007/978-0-387-74365-3.

Chowdhury, E.U., R. Eedson, L.A. Bisby, M.F. Green, N. Benichou, Mechanical characterization of fibre reinforced polymers materials at high temperature, *Fire Technol.* 47 (2011) 1063–1080, <http://dx.doi.org/10.1007/s10694-009-0116-6>.

Chi, S. H. and Chung, Y. L. (2006) ‘Mechanical behavior of functionally graded material plates under transverse load-Part I: Analysis’, *International Journal of Solids and Structures*, 43(13), pp. 3657–3674. doi: 10.1016/j.ijsolstr.2005.04.011.

Correia, J.R., M.M. Gomes, J.M. Pires, F.A. Branco, Mechanical behaviour of pultruded glass fibre reinforced polymer composites at elevated temperature: experiments and model assessment, *Compos. Struct.* 98 (2013) 303–313, <http://dx.doi.org/10.1016/j.compstruct.2012.10.051>.

Carlone, P., G.S. Palazzo, Unsaturated and saturated flow front tracking in liquid composite molding processes using dielectric sensors, *Appl. Compos. Mater.* 22 (2015) 543–557, <http://dx.doi.org/10.1007/s10443-014-9422-3>.

Czél, G., Pimenta, S., Wisnom, M. R. and Robinson, P. (2015) ‘Demonstration of pseudo-ductility in unidirectional discontinuous carbon fibre/epoxy prepreg composites’, *Composites Science and Technology*, 106, pp. 110–119. doi: 10.1016/j.compscitech.2014.10.022

Czaderski, C., E. Martinelli, J. Michels, M. Motavalli, Effect of curing conditions on strength development in an epoxy resin for structural strengthening, *Compos. Part B Eng.* 43 (2012) 398–410, <http://dx.doi.org/10.1016/j.compositesb.2011.07.006>.

Davies LW, Day RJ, Bond D, Nesbitt A, Ellis J, Gardon E. Effect of cure cycle heat transfer rates on the physical and mechanical properties of an epoxy matrix composite. *Composites Science and*

Technology. 2007 Jul 1;67(9):1892-9.

De Rosa, I. M., Santulli, C., Sarasini, F. and Valente, M. (2009) ‘Post-impact damage characterization of hybrid configurations of jute/glass polyester laminates using acoustic emission and IR thermography’, *Composites Science and Technology*. Elsevier Ltd, 69(7–8), pp. 1142–1150. doi: 10.1016/j.compscitech.2009.02.011.

Devi, L.U., Bhagawan, S.S. and Thomas, S. (2010) Dynamic mechanical analysis of pineapple leaf/glass hybrid fiber reinforced polyester composites. *Polymer composites*, 31(6), pp. 956-965.

Dekkers, M. E. J. and Heikens, D. (1983) ‘The Effect of Interfacial Adhesion on the Tensile Behavior of Polystyrene-Glass-Bead Composites’, 28, pp. 3809–3815.

Davies, L. W., Effect of cure cycle heat transfer rates on the physical and mechanical properties of an epoxy matrix composite, *Compos. Sci. Technol.* 67 (2007) 1892–1899, <http://dx.doi.org/10.1016/j.compscitech.2006.10.014>.

Esposito, L., L. Sorrentino, F. Penta, C. Bellini, Effect of curing overheating on interlaminar shear strength and its modelling in thick FRP laminates, *Int. J. Adv. Manuf. Technol.* 87 (2016) 2213–2220, <http://dx.doi.org/10.1007/s00170-016-8613-5>.

Fitler, E. (1989) Pan-based carbon fibers—present state and trend of the technology from the viewpoint of possibilities and limits to influence and to control the fiber properties by the process parameters. *Carbon*, 27(5), pp.621-645.

Fu, S. Y., Xu, G. and Mai, Y. W. (2002) ‘On the elastic modulus of hybrid particle/short-fiber/polymer composites’, *Composites Part B:Engineering*, 33(4), pp. 291–299. doi: 10.1016/S1359-8368(02)00013-6.

Fukuda, H. (1984) ‘An advanced theory of the strength of hybrid composites’, *Journal of Materials Science*, 19(3), pp. 974–982. doi: 10.1007/BF00540468.

Fukuda, H. and Chou, T. W. (2009) ‘Stress Concentrations in a Hybrid Composite Sheet’, *Journal of Applied Mechanics*, 50(4a), p. 845. doi: 10.1115/1.3167155.

Fu, S.Y. and Lauke, B. (1998) ‘Characterization of tensile behaviour hybrid short glass fibre / calcite particle / ABS composites of’, (97), pp. 575–583.

Furtos, G., L. Silaghi-Dumitrescu, M. Moldovan, B. Baldea, R. Trusca, C. Prejmerean, Influence of filler/reinforcing agent and post-curing on the flexural properties of woven and unidirectional glass fiber-reinforced composites, *J. Mater. Sci.* 47 (2012) 3305–3314, <http://dx.doi.org/10.1007/s10853-011-6169-1>.

Garlock ME, Quiel SE, Wang PY, Alós-Moya J, Glassman JD. Post-buckling mechanics of a square slender steel plate in pure shear. 2019 Jan 1;56(1):27-46.

Govignon Q, Bickerton S, Morris J, Kelly PA. Full field monitoring of the resin flow and laminate properties during the resin infusion process. *Composites Part A: Applied Science and Manufacturing*. 2008 Sep 1;39(9):1412-26.

Gopal, A.K., Adali, S., Verijenko, V.E., Optimal temperature profiles for minimum residual stress in the cure process of polymer composites, *Compos. Struct.* 48 (2000) 99–106, [http://dx.doi.org/10.1016/S0263-8223\(99\)00080-X](http://dx.doi.org/10.1016/S0263-8223(99)00080-X).

Giancaspro, J. W., Papakonstantinou, C. G. and Balaguru, P. N. (2010) ‘Flexural Response of Inorganic Hybrid Composites With E-Glass and Carbon Fibers’, *Journal of Engineering Materials and Technology*, 132(2), p. 021005. doi: 10.1115/1.4000670.

Gupta, V.B., Mittal, R.K., Sharma, P.K., Mennig, G. and Wolters, J. (1989) ‘Some Studies on Glass Fiber-Reinforced Polypropylene. Part II: Mechanical Properties and Their Dependence on Fiber Length, Interfacial Adhesion, and Fiber Dispersion’, 10(1).

Hayashi, T. (1972) ‘On the improvement of mechanical properties of composites by hybrid composition’, *Proc.8th Intl.Reinforced Plastics Conf.*, pp. 149–152. Available at: <http://ci.nii.ac.jp/naid/10004555738/en/> (Accessed: 2 April 2019).

Hogg, P. J., A. Ahmadnia, F.J. Guild, The mechanical properties of composites, *J. Compos. Mater.* 22 (1993) 423–432.

Iyengar NG, Chakraborty A. Study of interaction curves for composite laminate subjected to in-plane uniaxial and shear loadings. *Composite structures*. 2004 Jun 1;64(3-4):307-15.

Johnson, J.B., C.N. Owston, The effect of cure cycle on the mechanical properties of carbon-fibre/epoxide resin, *Composites* 4 (1973) 111–117, [http://dx.doi.org/10.1016/0010-4361\(73\)90584-3](http://dx.doi.org/10.1016/0010-4361(73)90584-3).

Joshi, M., Maiti, S.N., Misra, A. and Mittal, R.K. (1994) ‘and Interfacial Adhesion on Poly ( Butylene Ter ep h t ha la te ) / Pol yet h y lene Alloys Reinforced’, 15(5).

Jawaid, M. and Abdul Khalil, H. P. S. (2011) ‘Cellulosic/synthetic fibre reinforced polymer hybrid composites: A review’, *Carbohydrate Polymers*. Elsevier Ltd., 86(1), pp. 1–18. doi: 10.1016/j.carbpol.2011.04.043.

Jawaid, M., Abdul Khalil, H. P. S. and Abu Bakar, A. (2011) ‘Woven hybrid composites: Tensile and flexural properties of oil palm-woven jute fibres based epoxy composites’, *Materials Science and Engineering A*. Elsevier B.V., 528(15), pp. 5190–5195. doi: 10.1016/j.msea.2011.03.047.

John, K. and Naidu, S. V. (2004) ‘Tensile properties of unsaturated polyester-based sisal fiber - Glass fiber hybrid composites’, *Journal of Reinforced Plastics and Composites*, 23(17), pp. 1815–1819. doi: 10.1177/0731684404041147.

Jones, R.M. (1975) ‘Mechanics Of Composite Materials’, *McGraw-Hill, New York*, pp. 121-186.

Jain P, Kumar A. Postbuckling response of square laminates with a central circular/elliptical cutout. *Composite Structures*. 2004 Aug 1;65(2):179-85.

Kumar, D.S., M.J. Shukla, K.K. Mahato, D.K. Rathore, R.K. Prusty, B.C. Ray, Effect of post-curing on thermal and mechanical behavior of GFRP composites, IOP Conf. Ser.: *Mater. Sci. Eng.* 75 (2015) 012012, <http://dx.doi.org/10.1088/1757-899X/75/1/012012>

Kim YH, Noor AK. Buckling and postbuckling of composite panels with cutouts subjected to combined loads. *Finite elements in analysis and design*. 1996 Jun 1;22(2):163-85.

Kumar D, Singh SB. Stability and failure of composite laminates with various shaped cutouts under combined in-plane loads. *Composites Part B: Engineering*. 2012 Mar 1;43(2):142-49.

Kumar D, Singh SB. Load interaction curves and postbuckling response of composite laminate with circular cutout under combined in-plane loading. *Composites Part B: Engineering*. 2011 Jul 1;42(5):1189-95.

Kumar D, Singh SB. Effects of flexural boundary conditions on failure and stability of composite laminate with cutouts under combined in-plane loads. *Composites Part B: Engineering*. 2013 Feb 1;45(1):657-65.

Loughlan J, Hussain N. The post-buckled failure of steel plate shear webs with centrally located circular cut-outs. InStructures 2016 Nov 1; 8:252-263.

Lonetti P, Greco F, Zinno R, et al. (2003) Interlaminar damage model for polymer matrix composites. *Journal of Composite Materials* 37(16): 1485–1504

Liu, L., B. Zhang, D. Wang, Z. Wu, Eff. cure Cycles void Content Mech. Prop. Compos. Lamina. 73 (2006) 303–309, <http://dx.doi.org/10.1016/j.compstruct.2005.02.001>.

Liang, Y., Sun, C. and Ansari, F. (2004) ‘Acoustic Emission Characterization of Damage in Hybrid Fiber-Reinforced Polymer Rods’, *Journal of Composites for Construction*, 8(1), pp. 70–78. doi: 10.1061/(asce)1090-0268(2004)8:1(70).

Li, M.I.N., Q.I. Zhu, P.H. Geubelle, C.L. Tucker, Optimal curing of thermoset matrix composites: thermochemical considerations, *Polym. Compos.* 22 (2001) 1–32, <http://dx.doi.org/10.1002/pc.10524>.

Nordlund M, Michaud V. Dynamic saturation curve measurement for resin flow in glass fibre reinforcement. Composites Part A: Applied Science and Manufacturing. 2012 Mar 1;43(3):333-43.

Olivier, P., J.P. Cottu, B. Ferret, Effects of cure cycle pressure and voids on some mechanical properties of carbon/epoxy laminates, *Composites* 26 (1995) 509–515. [http://dx.doi.org/10.1016/0010-4361\(95\)96808-J](http://dx.doi.org/10.1016/0010-4361(95)96808-J).

Oluwabusi OE. Effect of central circular cut-out and low velocity impact damage on shear buckling and post-buckling of composite laminated plates. Composite Structures. 2020 Mar 30:112304.

Pandya, K. S., Veeraju, C. and Naik, N. K. (2011) ‘Hybrid composites made of carbon and glass woven fabrics under quasi-static loading’, *Materials and Design*. Elsevier Ltd, 32(7), pp. 4094–4099. doi: 10.1016/j.matdes.2011.03.003.

Pan, N., and Postle, R. (1996) ‘The tensile strength of hybrid fiber composites: A probabilistic analysis of the hybrid effects’ *Phil Trans R Soc London Ser a - Math Phys. Eng. Sci.*, 354, pp. 1875-97.

Pavithran, C., Mukherjee, P. S., Brahmakumar, M. and Damodaran, A. D. (1991) ‘Impact

properties of sisal-glass hybrid laminates', *Journal of Materials Science*, 26(2), pp. 455–459. doi: 10.1007/BF00576542.

Pavithran, C., Mukherjee, P. S., Brahmakumar, M. and Damodaran, A. D. (1991) 'Coir-glass intermingled fiber hybrid composites', *Journal of Reinforced Plastic Composites*, 10(1), pp. 91–101. doi: 10.1002/pc.23529.

Peijs, A. A. J. M. and de Kok, J. M. M. (1993) 'Hybrid composites based on polyethylene and carbon fibres. Part 6: Tensile and fatigue behaviour', *Composites*, 24(1), pp. 19–32. doi: 10.1016/0010-4361(93)90260-F.

Phillips, L. N. (1976) 'The hybrid effect — does it exist?', *Composites*, 7(1), pp. 7–8. doi: 10.1016/0010-4361(76)90273-1.

Pitkethly, M. J. and Bader, M. G. (1987) 'Failure modes of hybrid composites consisting of carbon fibre bundles dispersed in a glass fibre epoxy resin matrix', *Journal of Physics D: Applied Physics*, 20(3), pp. 315–322. doi: 10.1088/0022-3727/20/3/013.

Pukanszky, B., Belina, K., Rockenbauer, A. and Maurer, F. H. J. (1994) 'Effect of nucleation , filler anisotropy and orientation on the properties of PP composites', 25(3), pp. 205–214.

Ramsteiner, F. and Theysohn, R. (1984) 'On the tensile behaviour of filled composites', 15(2), pp. 121–128.

Rockey KC, Anderson RG, Cheung YK. The behaviour of square shear webs having a circular hole. InSymp. on Thin Walled Steel Structures, University College of Swansea 1967 Sep.

Rockey KC. The buckling and post-buckling behavior of shear panels which have a central circular cutout. Thin-Walled Structures: Recent Technical Advances and Trends in Design, Research and Construction. 1979 Apr:658-72.

Santulli, C., Janssen, M. and Jeronimidis, G. (2005) 'Partial replacement of E-glass fibers with flax fibers in composites and effect on falling weight impact performance', *Journal of Materials Science*, 40(13), pp. 3581–3585. doi: 10.1007/s10853-005-2882-y.

Singh SB, Kumar A. Postbuckling response and failure of symmetric laminates under in-plane shear. Composites science and technology. 1998 Dec 1;58(12):1949-60.

Singh SB, Kumar A. Postbuckling response and strength of laminates under combined in-plane loads. Composites science and technology. 1999 Apr 1;59(5):727-36.

Singh SB, Chawla H. Hybrid effect of functionally graded hybrid composites of glass–carbon fibers. Mechanics of Advanced Materials and Structures. 2019 Jul 18;26(14):1195-208.

Shindo, A. (1964) ‘On the carbonization of polyacrylonitrile fiber’, Carbon, 1, 391.

Singh, S. B., VummadiSETTI, S. and Chawla, H. (2018) ‘Influence of curing on the mechanical performance of FRP laminates’, Journal of Building Engineering, 16(August 2017), pp. 1–19. doi: 10.1016/j.jobe.2017.12.002.

Sreekala, M. S., George, J., Kumaran, M. G. and Thomas, S. (2002) ‘The mechanical performance of hybrid phenol-formaldehyde-based composites reinforced with glass and oil palm fibres’, Composites Science and Technology, 62(3), pp. 339–353. doi: 10.1016/S0266-3538(01)00219-6.

Swolfs, Y., Gorbatikh, L., Hine, P. J., Ward, I. M. and Verpoest, I. (2013) ‘Toughening of Carbon Fibre Composites By Hybridisation with Self-Reinforced Polypropylene’, 9th International Conference on Composite Science and Technology: 2020 - Scientific and Industrial Challenges, (April), pp. 495–502.

Swolfs, Y., Gorbatikh, L. and Verpoest, I. (2014) ‘Fibre hybridisation in polymer composites: A review’, Composites Part A: Applied Science and Manufacturing. Elsevier Ltd, 67, pp. 181–200. doi: 10.1016/j.compositesa.2014.08.027.

Thomas, M., M., B. Joseph, J.L. Kardos, Experimental characterization of autoclave cured glass-epoxy composite laminates: cure cycle effects upon thickness, void content, and related phenomena, *Polym. Compos.* 18 (1997) 283–299, <http://dx.doi.org/10.1002/pc.10282>.

Tang, M. and Bacon, R. (1964) ‘Carbonization of cellulose fibers—I. Low temperature pyrolysis’, Carbon, 2(3), pp. 211–220. doi: 10.1016/0008-6223(64)90035-1.

VummadiSETTI S, Singh SB. Buckling and postbuckling response of hybrid composite plates under uniaxial compressive loading. Journal of Building Engineering. 2020 Jan 1;27:101002.

Vummadietti S, Singh SB. Postbuckling response of functionally graded hybrid plates with cutouts under in-plane shear load. *Journal of Building Engineering*. 2020 **DOI:** [10.1016/j.jobe.2020.101530](https://doi.org/10.1016/j.jobe.2020.101530)

Wang, K., B. Young, S.T. Smith, Mechanical properties of pultruded carbon fibre reinforced polymer (CFRP) plates at elevated temperatures, *Eng. Struct.* 33 (2011) 2154–2161, <http://dx.doi.org/10.1016/j.engstruct.2011.03.006>.

Wang K, Zhao L, Hong H, Gong Y, Zhang J, Hu N. An analytical model for evaluating the buckling, delamination propagation, and failure behaviors of delaminated composites under uniaxial compression. *Composite Structures*. 2019 Sep 1;223:110937.

Wonderly, C., J. Grenestedt, G. Fernlund, E. Cepus, Comparison of mechanical properties of glass fiber/vinyl ester and carbon fiber/vinyl ester composites, *Compos. Part B Eng.* 36 (2005) 417–426, <http://dx.doi.org/10.1016/j.compositesb.2005.01.004>.

Yu, H., Longana, M. L., Jalalvand, M., Wisnom, M. R. and Potter, K. D. (2015) ‘Pseudo-ductility in intermingled carbon/glass hybrid composites with highly aligned discontinuous fibres’, *Composites Part A: Applied Science and Manufacturing*. Elsevier Ltd, 73, pp. 35–44. doi: 10.1016/j.compositesa.2015.02.014.

Zweben, C. (1977) ‘Tensile strength of hybrid composites’, *Journal of Materials Science*, 12(7), pp. 1325–1337. doi: 10.1007/BF00540846

Zhang J, Fox BL. Manufacturing influence on the delamination fracture behavior of the T800H/3900-2 carbon fiber reinforced polymer composites. *Materials and manufacturing processes*. 2007 Jun 29;22(6):768-72.